

# VOC'S CALCULATED FROM FORMULAS FOR CALIFORNIA® INTERIOR (AND INT/EXT) PAINTS\*

(All VOC's for "XX" designations calculated for pastel bases)

All VOC's are expressed in grams per liter (g/l)

<b>INTERIOR LATEX</b>		<u><b>VOCs</b></u>
2010 Super-Scrub® 100% Acrylic:		
Matte	553XX	95
Eggshell	551XX	141
Semi Gloss	552XX	148
<i>Flawless Elements™ Zero VOC:</i>		
Flat	733XX	0
Eggshell	731XX	0
Semi Gloss	763XX	0
Fres~Coat 100% Acrylic:		
Matte	532XX	97
Flat	533XX	49
Velvet Flat	535XX	91
Eggshell	531XX	125
Semi Gloss	563XX	137
Pacific® Acrylic:		
Flat	560XX	48
Eggshell	561XX	130
Semi Gloss	559XX	148
Kitchen & Bath 100% Acrylic w/Microban:		
Eggshell	512XX	140
Semi Gloss	513XX	148
Envirotech™ Zero VOC:		
Flat	633XX	0
Eggshell	631XX	0
Semi Gloss	663XX	0
Pro2000 Acrylic Latex:		
Flat	556XX	48
Eggshell	557XX	110
Semi Gloss	558XX	147
ProPaint® Latex:		
Flat	508XX	48
Eggshell	509XX	125
Semi Gloss	510XX	142
Preference® Latex:		
Flat	501XX	92
Semi Gloss	502XX	108
Contractor Latex:		
Flat	51600	77
Semi Gloss	51700	98

**PRIMERS, INTERIOR LATEX****VOCs**Prime Choice<sup>®</sup>:

All Surface	50300	155
AllWall	56600	124
Universal	50600	79

Prime Touch<sup>®</sup>:

Primer Sealer	54500	110
Enamel Undercoater	54700	96

Grip-Coat<sup>®</sup>:

Bonding Primer	50500	<u>117</u>
----------------	-------	------------

## Preference:

Primer	50000	97
--------	-------	----

## Contractor:

Primer	54400	93
--------	-------	----

Wipe-Out<sup>®</sup>:

Primer	52500	114
--------	-------	-----

## Envirotech Zero VOC:

Primer	64600	0
--------	-------	---

*Flawless Elements*<sup>™</sup> Zero VOC:

Primer	74600	0
--------	-------	---

**PRIMERS, INTERIOR OIL**Prime Choice<sup>®</sup>:

Alkyd	20200	336
Low Odor	20700	348

## Metal Primer (Oil):

Larcoloid <sup>®</sup>	21150	333
------------------------	-------	-----

## Metal Primer Latex (Int./Ext.):

Rust Stop <sup>®</sup>	1061	95
------------------------	------	----

**CEILING WHITES (LATEX)**

Diamond	54100	90
Pacific	54000	95
Pro2000	55500	73
Latex CW	53900	92

**FLOOR (& MULTIPURPOSE) COATINGS LATEX**

AllFlor <sup>®</sup>	530XX	144
Wear-All <sup>®</sup>	528XX	175

		<u>VOCs</u>
<b>FLOOR COATINGS OIL</b>		
Tuf-Quik®	205XX	336
Ox-O-Deck®	708XX	331
Wear-All	243XX	247
<b>INT./EXT.</b>		
Larcoloid 100% Acrylic Latex:		
Gloss Enamel	511XX	248
Wear-All Multipurpose:		
Gloss Enamel	242XX	331
Larcoloid Alkyd Urethane:		
Gloss Enamel	21XX	335
Fres~Coat Alkyd		
Semi Gloss	210XX	336
<b>BLOCK FILLERS</b>		
Mason-Cote® 100% Acrylic Latex	3751	65
ProPaint® Latex	51500	69

\* Please note: The specification sheets for all of these products show the “MAX. VOC” levels. These are the maximum levels allowed by regulatory agencies in most areas and can be significantly different from the VOC levels calculated from the formulas. Some specifications require the actual levels of VOC’s so the “Max” levels are not helpful. This is why we are providing this list.

For any further questions about calculated VOC’s for the above paints or other California Paints product VOC’s, please contact: Ronald B. Child, VP, Compliance & Regulatory Affairs at 1-800-225-1141, ext. \*223 (Must use star) or [r.child@calprocorp.com](mailto:r.child@calprocorp.com).

Ref. 452-01 (Revised 5/16/11)