



ALUMINUM & VINYL SIDING

REPRESENTATIVE SURFACES

- Homes
- Commercial Buildings

GENERAL

Vinyl or aluminum siding fades and oxidizes with time. These surfaces are excellent materials to paint because, unlike finished wood, there is no moisture transmission or splitting, checking and cracking.

100% Acrylics directly applied to properly prepared surfaces make excellent coatings because of their flexibility, oxidation resistance and color retention. Always paint vinyl siding with a similar or lighter color since dark colors absorb heat and can cause warping or buckling. Satin Gloss Acrylic provides the longest lasting finish and approximates the original sheen of the siding.

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

- Pressure wash at a minimum 2200 PSI or hand scrub to remove surface contamination and oxidation.
- Rinse thoroughly with water and allow to dry.

PRIMERS

None required.



PRODUCT RECOMMENDATIONS - ALUMINUM & VINYL SIDING

PRIMERS	FINISH COATS
<ul style="list-style-type: none">• None Required	<ol style="list-style-type: none">1. 2010[®] Exterior 100% Acrylic Flat, Eggshell* or Satin Gloss*2. Fres~Coat 100% Acrylic Latex House Paint Velvet Flat3. Fres~Coat 100% Acrylic Latex Satin Gloss House & Trim*

*Best Finishes