

**CEMENT, COMPOSITION SIDING & PANELS****REPRESENTATIVE SURFACES**

Siding Boards
Soffits
Panels

GENERAL

This exterior siding material is a cement based product or a mixture of cement with wood fibers that is formed into either horizontal siding or vertical paneling.

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Pressure wash or hand scrub to remove any surface contamination. If surface is chalky, apply a coat of Stonite® Masonry Conditioner #7010.

PRIMERS

- Troubleshooter® 100% Acrylic Latex Primer (only if wood fiber content is high enough to cause bleed through).
- Acrylic Latex finishes directly to sound surfaces.



PRODUCT RECOMMENDATIONS - CEMENT COMPOSITION

PRIMERS	FINISH COATS
<ul style="list-style-type: none">• Stonite® Waterborne Acrylic Masonry Primer #7007 (only if surface is chalky)• Fres~Coat Troubleshooter® 100% Acrylic Latex Primer (only if wood fiber content is high enough to cause bleed through)	<ol style="list-style-type: none">1. 2010® Exterior 100% Acrylic Flat, Eggshell or Satin Gloss2. Fres~Coat 100% Acrylic Latex House Paint Velvet Flat3. Fres~Coat 100% Acrylic Latex Satin Gloss House & Trim4. Pacific® Latex Flat5. Pacific Latex Satin Gloss