



**CERAMIC TILE**

**REPRESENTATIVE SURFACES**

- Walls
- Ceilings
- Sanitary Fixtures

**SURFACE PREPARATION**

- 1) Wash with 20% Muriatic Acid
- 2) Rinse with clean water
- 3) Dry thoroughly before applying finish coats.

**PRIMERS**

Use GRIP-COAT® #6906 Vinyl Wash Primer as a tie-coat to insure adhesion of the finish coat.

**CERAMIC TILE**

**PRODUCT RECOMMENDATIONS — CERAMIC TILE**

EXPOSURE CONDITIONS	PRIMER	TOPCOAT
<b>Indoor Exposure To Water</b> - immersion, frequent washing with strong soaps and detergents, urine, and strong acids and alkalis.	GRIP-COAT® 6906 VINYL WASH PRIMER	TILE-COTE® EPOXY 1200 SERIES
<b>Exterior Exposure</b> to weathering and salt spray	GRIP-COAT 6906 VINYL WASH PRIMER	TUF-FLEX® ACRYLIC EPOXY 1300 SERIES
<b>Apply to Damp Surfaces</b> Interior only	GRIP-COAT 6906 VINYL WASH PRIMER	SUPER DAMPCOAT® II 1901 WHITE SANITARY ENAMEL