



Contractor Ceiling White

53900

Product Description:

Ceiling White is a smooth flowing general purpose ceiling white formulated with the professional applicator in mind. It provides good hide and uniform appearance with high production application.

Recommended Use:

Sheetrock, wallboard, concrete, wood, primed metal, acoustical surfaces, sand and texture finish ceiling.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. Ceiling White is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.
 Ferrous Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer
 Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer
 Masonry Block - Apply one coat of ProPaint Block Filler 51500 if a denser surface is desired.

Architectural Specifications:

- Wallboard, Sheetrock:
1 or 2 coats Ceiling White 53900
- Concrete, Non-Porous Masonry:
1 or 2 coats Ceiling White 53900
- Porous Masonry and Block:
1 coat ProPaint® Block Filler 51500
1 or 2 coats Ceiling White 53900
- Ferrous Metal - Un-primed:
1 coat Larcoloid® Rust Inhibiting Metal Primer 21150
1 or 2 coats Preference Semi-Gloss 502XX
- Galvanized Metal:
1 coat Larcoloid Acrylic Latex Rust Inhibiting Metal Primer
1 or 2 coats Ceiling White 53900

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: Vinyl Acrylic Latex
Exposure: Interior
Specular Gloss: 2 @ 60° ± 2
Volume Solids: 32.3 % ± 2
Solids by Weight: 52.8 % ± 2
Vehicle: 53.8 % ± 2
Pigment: 46.2 % ± 2
Dry Film Thickness: 1.4 mils
Viscosity @ 77 °F: 103 KU ± 5
Maximum VOC: 100 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White

Available Package Sizes:

Gallon 5 Gallon

(Weight Per Gallon: 12.0 lbs. ± .5 lb)

Drying Times:

To Touch: .5 hrs.
To Handle: 4 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 350-400 s.f./gal.
Porous: 250-300 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.017 to .019 Tip