



Diamond Acrylic Latex Ceiling White

54100

<p>Product Description:</p> <p>Diamond Acrylic Ceiling White is the highest quality ceiling white available today. The anti-spatter formulation provides the industry standard for whiteness, hiding power, adhesion, color retention, and leveling. For both ease of application and long term durability, this is the finest product for most interior ceiling surfaces.</p>	<p>Product Specifications:</p> <p>Type: Vinyl Acrylic Latex Exposure: Interior Specular Gloss: @ 60° ± 2 Volume Solids: 32.0 % ± 2 Solids by Weight: 52.0 % ± 2 Vehicle: 56.6 % ± 2 Pigment: 43.4 % ± 2 Dry Film Thickness: 1.2 mils Viscosity @ 77 °F: 95 KU ± 5 Maximum VOC: 100 g/liter Flash Pt °F: Non-cumbustible Thinner: Water Clean Up: Soap & Water</p>
<p>Recommended Use:</p> <p>Plaster, sheetrock, wallboard, concrete, wood, primed metal, acoustical surfaces, sand and texture finish ceilings.</p>	
<p>Application:</p> <p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. Diamond Acrylic Ceiling White is self-priming ove bare sheetrock, composition board, ceiling tile and concrete.</p> <p>New plaster: knife off all nibs and protusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board: joint compound should be sanded smooth, but avoid abrading paper. Ferrous Metal: clean, then prime with Larcoloid Rust Inhibiting Metal Primer. Wood: seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer. Masonry Block: Apply one coat of Mason-Coat Block Filler 3751 if denser surface is desired.</p>	<p>Available Colors and Bases:</p> <p>White</p>
<p>Architectural Specifications:</p> <ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock: <ul style="list-style-type: none"> 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Concrete, Non-Porous Masonry: <ul style="list-style-type: none"> 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Porous Masonry and Block: <ul style="list-style-type: none"> 1 coat Mason-Cote® Block Filler 3751 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Ferrous Metal - Un-primed: <ul style="list-style-type: none"> 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Galvanized Metal: <ul style="list-style-type: none"> 1 coat Larcoloid Acrylic Latex Rust Inhibiting Metal Primer 51106, 51108, 51106 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Wood: <ul style="list-style-type: none"> 1 coat Prime Choice™ All Surface Acrylic Primer 50300 1 or 2 coats Diamond Acrylic Latex Ceiling White 54100 ▪ Acoustical Tile: <ul style="list-style-type: none"> 2 coats 2010 Diamond Acrylic Latex Ceiling White 54100 	<p>Available Package Sizes:</p> <p>Quart Gallon 2 Gallon</p> <p>5 Gallon</p> <p>(Weight Per Gallon: 11.9 lbs. ± .5 lb)</p> <p>Drying Times:</p> <p>To Touch: .5 hrs. To Handle: 2 hrs. To Recoat: 2 hrs.</p> <p>(@ 70-77 °F, 50% R.H.)</p>
<p>Precautions:</p> <p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p>	<p>Surface Spread Rate:</p> <p>Smooth: 400-450 s.f./gal. Porous: 350-400 s.f./gal.</p> <p>(Spray Application is 50% of above)</p>
<p>Safety Information:</p> <p>Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p>Tools and Equipment:</p> <p>Brush - Synthetic, Nylon or Polyester</p> <p>Roller - 3/8" Nap Synthetic Fiber</p> <p>Airless Spray .017 to .019 Tip</p>