



flawless ELEMENTS™ Zero VOC Interior Acrylic Latex Ceiling Flat with Microban® 74100

Product Description:

flawless ELEMENTS™ Zero VOC Flat Ceiling White is an environmentally preferred, premium quality interior ceiling paint that provides flawless application and exceptional durability with essentially no odor during and after painting. Room and office ceilings painted with flawless ELEMENTS Zero VOC Flat Ceiling White can be occupied right away without a compromise to healthy indoor air quality. With Microban® antimicrobial protection, flawless ELEMENTS provides an added level of mildew resistance not found in other Zero VOC paints.

Recommended Use:

Plaster, sheetrock, wallboard, concrete, wood, primed metal, acoustical surfaces, sand and texture finish ceilings.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

New plaster: knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board: joint compound should be sanded smooth, but avoid abrading paper.

Ferrous Metal: clean, then prime with Larcoloid Rust Inhibiting Metal Primer.

Wood: Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer.

Masonry Block: Apply one coat of Mason-Coat Block filler 3751 if denser surface is desired.

Architectural Specifications:

- Plaster, Wallboard, Sheetrock:
 - 1 coat flawless ELEMENTS Zero VOC Interior 100% Acrylic Latex Primer-Sealer 74600 or
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Concrete, Non-Porous Masonry:
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Porous Masonry and Block:
 - 1 coat Mason-Cote® Block Filler 3751
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Ferrous Metal - Un-primed:
 - 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Galvanized Metal:
 - 1 coat Larcoloid Acrylic Latex Rust Inhibiting Metal Primer 51106, 51108, 51106
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Wood:
 - 1 coat flawless ELEMENTS Zero VOC Interior 100% Acrylic Latex Primer-Sealer 74600
 - 1 or 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100
- Acoustical Tile:
 - 2 coats flawless ELEMENTS Zero VOC Interior Acrylic Latex Ceiling Flat with Microban 74100

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: Vinyl Acrylic Latex
Exposure: Interior
Specular Gloss: 2 @ 60° ± 2
Volume Solids: 31.9 % ± 2
Solids by Weight: 52.0 % ± 2
Vehicle: 56.6 % ± 2
Pigment: 43.4 % ± 2
Dry Film Thickness: 1.2 mils
Viscosity @ 77 °F: 95 KU ± 5
Maximum VOC: Calc. 0g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White

Available Package Sizes:

Quart Gallon 5 Gallon

(Weight Per Gallon: 11.8 lbs. ± .5 lb)

Drying Times:

To Touch: .5 hrs.
To Handle: 2 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 400-450 s.f./gal.
Porous: 350-400 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray
.017 to .019 Tip