



Pro 2000® Latex Ceiling Flat White

55500

<p>Product Description: PRO 2000 LATEX CEILING FLAT WHITE is an anti-splatter, smooth flowing general purpose ceiling white formulated with the professional applicator in mind. It provides a high hiding smooth finish and uniform appearance with high production application.</p>	<p>Product Specifications: Type: Vinyl Acrylic Latex Exposure: Interior Specular Gloss: 2 @ 60° ± 2 Volume Solids: 31.7 % ± 2 Solids by Weight: 51.4 % ± 2 Vehicle: 57.3 % ± 2 Pigment: 42.7 % ± 2 Dry Film Thickness: 1.4 mils Viscosity @ 77 °F: 107 KU ± 5 Maximum VOC: 100 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p>
<p>Recommended Use: Plaster, sheetrock, wallboard, concrete, wood, primed metal, acoustical surfaces, sand and texture finish ceiling.</p>	
<p>Application: WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead. Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. PRO 2000 LATEX CEILING FLAT WHITE is self-priming over bare sheetrock, composition board, ceiling tile and concrete. New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper. Ferrous Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer. Masonry Block - Apply one coat of Mason-Cote® Block Filler 3751 if a denser surface is desired.</p>	<p>Available Colors and Bases: White</p>
<p>Architectural Specifications:</p> <ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock: 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Concrete, Non-Porous Masonry: 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Porous Masonry and Block: 1 coat ProPaint® Block Filler 51500 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Ferrous Metal - Un-primed: 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Galvanized Metal: 1 coat Larcoloid® Acrylic Latex Rust Inhibiting Metal Primer, White 51106, Gray 51108, Red 51107 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Wood: 1 coat Prime Choice™ All Surface Acrylic Primer 50300 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 ▪ Acoustical Tile: 1 or 2 coats Pro 2000 Latex Ceiling Flat White 55500 	<p>Available Package Sizes: Gallon 5 Gallon (Weight Per Gallon: 11.8 lbs. ± .5 lb)</p> <p>Drying Times: To Touch: .5 hrs. To Handle: 4 hrs. To Recoat: 2 hrs. (@ 70-77 °F, 50% R.H.)</p>
<p>Precautions: Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p>	<p>Surface Spread Rate: Smooth: 350-400 s.f./gal. Porous: 250-300 s.f./gal. (Spray Application is 50% of above)</p>
<p>Safety Information: Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p>Tools and Equipment: Brush - Synthetic, Nylon or Polyester Roller - 3/8" Nap Synthetic Fiber Airless Spray - .017 to .019 Tip</p>