



# INDUSTRIAL

Interior or Exterior

## Larcoloid® Aluminum 21110

### Product Description:

This all purpose chrome aluminum finish provides the outstanding rust inhibiting features of three types of aluminum pigment in a single self-priming coating. It will reflect 70% of the sun's destructive rays and withstands years of adverse climatic conditions.

### Recommended Use:

Roof decks, fire escapes, railing, equipment, chain link fence, tanks, transmission towers, ventilating units

### Application:

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Surface Preparation:** Surfaces to be painted must be free of dust, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination.

- New Plaster - Knife off all nubs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.
- Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.
- Ferrous Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer.
- Wood - Sand smooth and remove dust.
- Masonry Block - Apply one coat of Mason-Cote Block Filler 3751.
- Previously Painted Surfaces - Wash, sand or dust to obtain a paintable surface.
- Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.

### Architectural Specifications:

- Ferrous Metal - Un-primed
  - 1 coat Larcoloid Rust Inhibiting Alkyd Metal Primer 21150
  - 1 or 2 coats Larcoloid Aluminum 21110
- Ferrous Metal - Primed:
  - 1 or 2 coats Larcoloid Aluminum 21110
- Previously Painted Surfaces:
  - 1 or 2 coats Larcoloid Aluminum 21110

### Precautions:

Do not mix with water, oils or colors in oil, or mix with other paints. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Not recommended as a house paint primer. For maximum rust inhibiting requirements prime bare ferrous metal with Prime-Line® Metal Primer.

### Safety Information:

**CAUTION! COMBUSTIBLE!** Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

### Product Specifications:

**Type:** Hydrocarbon  
**Exposure:** Interior or Exterior  
**Specular Gloss:** NA@ 60°±  
**Volume Solids:** 43.9% ±2  
**Solids by Weight:** 52.7% ±2  
**Vehicle:** 89.9% ±2  
**Pigment:** 10.1% ±2  
**Dry Film Thickness:** 1.9 mils  
**Viscosity @ 77 °F:** KU ±  
**Maximum VOC:** 500 g/liter  
**Flash Pt °F:** 103  
**Thinner:** Mineral Spirits  
**Clean Up:** Mineral Spirits

### Available Colors and Bases:

Bright Alum.

### Available Package Sizes:

Pint      Quart      Gallon

(Weight Per Gallon: 8.2 lbs. ± .5 lb)

### Drying Times:

**To Touch:** 10 hrs.  
**To Handle:** 16 hrs.  
**To Recoat:** 16 hrs.

(@ 70-77 °F, 50% R.H.)

### Surface Spread Rate:

**Smooth:** 350-400 s.f./gal.  
**Porous:** 250-300 s.f./gal.

(Spray Application is 50% of above)

### Tools and Equipment:

**Brush -**  
Natural Bristle

**Roller -**  
3/8" Nap Synthetic Fiber or Natural Bristle

**Airless Spray -**  
.012 to .015 Tip