



Fres~Coat Oil House & Trim Paint Gloss

21800

Product Description:

Fres~Coat Gloss Oil House & Trim Paint is a high quality alkyd finish fortified with rich natural linseed oil to provide a flexible long lasting finish on exterior wood siding and trim. This fume and weather resistant paint flows smoothly and dries to a pleasing and durable satin gloss finish. Gloss Oil House & Trim Paint is available in the most desired contemporary and historical colors for all types of wood siding and trim finishes.

Recommended Use:

Clapboards, shingles, shakes, shutters, trim

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces must be clean and free of surface contamination. On previously painted surfaces, remove all loose or scaly paint by sanding or scraping so that all remaining paint is tightly adhered to the surface. Spot prime all bare spots or badly eroded areas with Troubleshooter® 100% Acrylic Latex Primer or Troubleshooter Alkyd/Linseed Oil Wood Primer. All mildewed areas should be washed down with a solution of equal parts household bleach and water. Rinse thoroughly with clean water and allow to dry before painting. Wear rubber gloves and safety goggles for personal protection during application. Caulk all holes and joints around windows, doors, trim, clapboards and other openings with California Caulking Compound. Gloss Oil House & Trim Paint can be applied directly to any properly prepared previously painted surface. Apply paint generously and uniformly. Do not brush out excessively. In hot weather work on shady side of building if possible.

New Wood, Shingles, Shakes, Clapboards, Trim, Plywood, Texture I-II - Spot prime knots with Wipe-Out®, Wipe-Out Low Odor or Wipe-Out 100% Acrylic Stain Block before priming entire surface with Fres~Coat Troubleshooter Alkyd/Linseed Oil Wood Primer or Trouble Shooter 100% Acrylic Latex Primer. If brown stains show through cedar or other redwoods after priming, these areas should be primed again before finish painting.
 Ferrous Metal - All bare metal must be primed with Larcoloid® Rust Inhibiting Metal Primer before finish coating with Gloss Oil House & Trim Paint to avoid rusting.

Architectural Specifications:

Precautions:

Surfaces to which paint is to be applied must be dry to touch. Do not apply on damp, humid or foggy days, when rain is imminent or in late afternoon when there is a threat of moisture condensing on the paint film. This is to avoid the possibilities of wrinkling or loss of gloss of the paint film. Air and surface temperature should be 40 ° F or higher during application and drying. Low temperatures or high humidity will greatly lengthen the normal drying time. Do not mix with other paints, linseed oil, special thinners or water. For maximum color retention properties and resistance to moisture peeling use California 100% Acrylic Latex House Paint. Gloss Oil House & Trim Paint is resistant to the deteriorating action of mildew and bacteria. No claim is made for the preservative action to other than the paint film.

Safety Information:

CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: Alkyd Linseed Oil
Exposure: Exterior
Specular Gloss: 60@ 60° ± 5
Volume Solids: 61.2 % ±2
Solids by Weight: 78.4 % ±2
Vehicle: 52.5 % ±2
Pigment: 47.5 % ±2
Dry Film Thickness: 2.5 mils
Viscosity @ 77 °F: 80 KU ±5
Maximum VOC: 380 g/liter
Flash Pt °F: 103
Thinner: Mineral Spirits
Clean Up: Mineral Spirits

Available Colors and Bases:

White

Available Package Sizes:

Quart Gallon

(Weight Per Gallon: 11.6 lbs. ± .5 lb)

Drying Times:

To Touch: 16-20 hrs.
To Handle: 24 hrs.
To Recoat: 48 hrs.
 (@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 375-425 s.f./gal.
Porous: 250-300 s.f./gal.
 (Spray Application is 50% of above)

Tools and Equipment:

Brush -
 Natural Bristle

Roller -
 3/8" Nap Synthetic Fiber

Airless Spray -
 0.011 to 0.013 Tip