



California Hi-Hide Line Marking Paint

6020 White; 6220 Textured White

Product Description:

Highly reflective marking paint for use over any bituminous surface or color coating system in recreational or light traffic areas. The finished application is non-glaring, highly resistant to climatic conditions, fast drying, easily applied, and provides excellent hiding. California Hi-Hide Line Marking Paint will not cause crazing, cracking, peeling or deterioration to asphalt that is typical of solvent-type traffic paints. Also available as a texture line paint containing fine silica fillers. Other colors available on request.

Recommended Use:

Marking of Recreational Surfaces, Parking Lots, Curbs, Berms

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

The surface must be clean, sound, free of dust, dirt, oil, grease and loose particles. For repainting, remove chalky surface dust by power washing surface with a stiff bristle brush and water.

Application:

Apply by nylon brush or pressure-type spray equipment, snap chalk lines to give side limits for brush application, use template or tape lines with double wide tape applicators. Test spray gun for proper nozzle and pressure to prevent overspraying. Do not atomize. Use pressure only. This product is ready to use from container. If thinning is required on hot dry surface, add only clear water. Apply evenly and uniformly. Use care in kneeling or walking on surfaces during application to prevent indentations of surrounding areas.

Architectural Specifications:

- California Hi-Hide Line Marking Paint is a 100% acrylic latex type formulated especially for use over sand-filled 100% acrylic recreational surfaces or directly on bituminous surfaces including emulsified asphalt and tar emulsion types. Plexicolor will not cause lifting, cracking, peeling or other damage to the base. White Plexicolor will not yellow.

Precautions:

Do not mix with oils, solvents or other paints.
Do not apply when air or surface temperature is below 50°F or when rain or high humidity is imminent.
Apply when ambient temperature is 50°F and rising.
Do not apply if surface temperature is in excess of 140°F.
Allow asphalt surfaces to cure 14 days before application.
STORE IN A COOL PLACE, NEVER IN THE HOT SUN.
Do not allow to run or drip on adjacent areas. Remove any drips immediately with water before drying occurs. Clean all brushes and equipment with water immediately after use.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

CAUTION

This product contains more than 0.1% crystalline silica (CAS No. 14808-60-07) which has been classified by IARC as a Class 1 carcinogen. Normal application procedures pose no hazard since the silica is wet and encapsulated, but grinding or sanding dried films may yield respirable silica dusts. Control exposures to less than 0.1 mg/m³ using NIOSH approved dust filter respirators.

* Data supplied is based on Plexicolor 6020 White. Other colors available.

Product Specifications:

Type: 100% Acrylic Latex*
Exposure: Interior or Exterior
Specular Gloss: 2 @ 60° ± 2
Volume Solids: 35.0 % ± 2
Solids by Weight: 53.0 % ± 2
Vehicle: 64.6 % ± 2
Pigment: 35.4 % ± 2
Dry Film Thickness: 2-3 mils
Viscosity @ 77 °F: -95 KU ± 5
Maximum VOC: 100 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White	Textured White
Yellow	Green
Red	Orange
Blue	Black

Available Package Sizes:

Gallon 5 Gallon

(Weight Per Gallon: 11.6 lbs. ± .5 lb)

Drying Times:

To Touch: .5 hrs.
To Handle: 1 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 200 s.f./gal.
Porous: 150 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.017 to .019 Tip