



# Wear-All® Multipurpose Alkyd High Gloss Enamel\*

## 243XX

<b>Product Description:</b>	<b>Product Specifications:</b>
Wear-All® Multipurpose Alkyd Gloss Enamel is a durable, smooth flowing gloss finish enamel formulated to protect a variety of interior or exterior surfaces. It provides an economical finish for most surfaces in homes, offices and public buildings. This all-purpose enamel will withstand repeated detergent washings without injury to the paint and can be readily recoated when necessary.	<b>Type:</b> Alkyd <b>Exposure:</b> Interior or Exterior <b>Specular Gloss:</b> 73 @ 60° ± 3 <b>Volume Solids:</b> 56.1 % ± 2 <b>Solids by Weight:</b> 71.3 % ± 2 <b>Vehicle:</b> 69.7 % ± 2 <b>Pigment:</b> 30.3 % ± 2 <b>Dry Film Thickness:</b> 2 mils <b>Viscosity @ 77 °F:</b> 85 KU ± 5 <b>Maximum VOC:</b> 250 g/liter <b>Flash Pt °F:</b> 103 <b>Thinner:</b> Mineral Spirits <b>Clean Up:</b> Mineral Spirits
<b>Recommended Use:</b>	<b>Available Colors and Bases:</b>
Floors • Decks • Woodwork • Cabinets • Trim • Equipment • Furniture • Metal	White 8 Stock Pastel Medium Deep Neutral
<b>Application:</b>	<b>Available Package Sizes:</b>
<p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>.</p> <p>Surfaces to be painted must be free of dust, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. On new wood or concrete surfaces WearAll Alkyd High Gloss Enamel is self-priming. Apply as thinly as possible using a multi-coat system on new surfaces.</p> <p>Ferrous Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer.            Wood - New wood should be clean, dry and sanded if necessary.            Previously Painted Surfaces - Wash, sand or dust and remove any loose paint to obtain a paintable surface.            Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.            Concrete - Porous or dusty concrete must be sealed with Stonite® Masonry Conditioner. New concrete must cure a minimum of 30 days and have a moisture content below 15%. Steel troweled smooth concrete with hardeners or curing membranes may require abrasion to obtain proper adhesion.</p>	Gallon 5 Gallon  (Weight Per Gallon: 10.5 lbs. ± .5 lb)
<b>Architectural Specifications:</b>	<b>Drying Times:</b>
<ul style="list-style-type: none"> <li>▪ Wood: 2 coats Wear-All Multi-Purpose Alkyd High Gloss Enamel 243XX</li> <li>▪ Concrete, Non-Porous Masonry: 2 coats Wear-All Multi-Purpose Alkyd High Gloss Enamel 243XX</li> <li>▪ Porous Masonry and Block: 1 coat Mason-Cote® Block Filler 3751 1 or 2 coats Wear-All Multi-Purpose Alkyd High Gloss Enamel 243XX</li> <li>▪ Ferrous Metal - Un-primed: 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150 1 or 2 coats Wear-All Multi-Purpose Alkyd High Gloss Enamel 243XX</li> </ul>	<b>To Touch:</b> 4-6 hrs. <b>To Handle:</b> 16 hrs. <b>To Recoat:</b> 24 hrs. (@ 70-77 °F, 50% R.H.)
<b>Precautions:</b>	<b>Surface Spread Rate:</b>
Do not add water, oils or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Do not apply to concrete below ground or directly on moist ground without thoroughly etching. Inadequate ventilation, high humidity, low temperatures or thick applications will greatly retard drying time.	<b>Smooth:</b> 400-450 s.f./gal. <b>Porous:</b> 250-350 s.f./gal. (Spray Application is 50% of above)
<b>Safety Information:</b>	<b>Tools and Equipment:</b>
<p>CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.</p> <p>Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. If this product is swallowed, call a physician immediately. Never give anything by mouth to an unconscious person. Treat symptomatically.</p> <p>NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.</p> <p>*This product has been specifically formulated to meet the VOC requirements of the northeast Ozone Transport Commission (OTC) for a maximum VOC of 250g/l (level set for gloss paints and coatings).</p>	<b>Brush -</b> Synthetic, Nylon or Polyester  <b>Roller -</b> Short Nap Synthetic or Natural Fiber  <b>Airless Spray -</b> 0.011 to 0.013 Tip