



2010 Super-Scrub® Ceramic Matte With Microban 553XX

Product Description:

2010 Super-Scrub Ceramic Matte Finish is the highest quality, smooth flowing, quick drying, anti-spatter waterborne matte finish for interior walls and ceilings in homes, apartments and public buildings. It is self leveling, has excellent color retention and is washable for years of service. 2010 Super-Scrub Ceramic Matte Finish has outstanding scrubability. This product has unique stain removal characteristics, so effective that even lines from most magic markers can be removed with ease. Ceramic Microspheres are the latest in waterborne paint technology. When incorporated with a 100% acrylic waterborne vehicle they impart the most durable stain resistant finish available. 2010 Super-Scrub Ceramic Matte Finish contains Microban antimicrobial product protection. This unique additive will inhibit the growth of stain and odor causing bacteria; mold, mildew and other fungal growth on the dried paint film. Microban protection provides an added level of protection between cleanings, but does not take the place of normal cleaning and disinfecting procedures and will not protect users or others against food borne illness. Microban additives are E.P.A. registered for use in paint.

Recommended Use:

Plaster, sheetrock, wallboard, concrete, masonry block, wood, primed metal, galvanized metal, acoustical surfaces.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure.

Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

2010 Super-Scrub Ceramic Matte Finish requires thorough stirring prior to application. Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. 2010 Super-Scrub Ceramic Matte Finish is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

- New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.
- Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.
- Ferrous Metal - Clean, then prime with Larcoloid Rust Inhibiting Metal Primer.
- Wood - Seal knots and stains with Wipe-Out, Wipe-Out Low Odor or Wipe-Out 100% Acrylic Stain Block.
- Masonry Block - Apply one coat of Mason-Cote Block Filler if a denser surface is desired.

Architectural Specifications:

- Plaster, Wallboard, Sheetrock: 2 coats 2010 Super-Scrub Ceramic Matte Finish
- Concrete, Non-Porous Masonry: 2 coats 2010 Super-Scrub Ceramic Matte Finish
- Porous Masonry and Block: 1 coat Mason-Cote® Block Filler 3751
1 or 2 coats 2010 Super-Scrub Ceramic Matte Finish
- Ferrous Metal - Un-primed: 1 coat Larcoloid® Rust Inhibiting Metal Primer
1 or 2 coats 2010 Super-Scrub Ceramic Matte Finish
- Ferrous Metal - Primed, Galvanized Metal:
2 coats 2010 Super-Scrub Ceramic Matte Finish
- Wood:
1 coat 100% Acrylic Enamel Undercoat 54600 or ASAP® 50300
1 or 2 coats 2010 Super-Scrub Ceramic Matte Finish
- Acoustical Tile:
2 coats 2010 Super-Scrub Ceramic Matte Finish

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: 100% Acrylic Latex
Exposure: Interior
Specular Gloss: 2 @ 60° ± 2
Volume Solids: 28.4 % ± 2
Solids by Weight: 44.5 % ± 2
Vehicle: 68.7 % ± 2
Pigment: 31.3 % ± 2
Dry Film Thickness: 1.3 mils
Viscosity @ 77 °F: 93 KU ± 5
Maximum VOC: 100 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White Pastel
 Medium

Available Package Sizes:

Quart Gallon 5 Gallon

(Weight Per Gallon: 10.8 lbs. ± .5 lb)

Drying Times:

To Touch: 1 hrs.
To Handle: 4 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 350-400 s.f./gal.
Porous: 250-300 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
 Synthetic, Nylon or Polyester

Roller -
 3/8" Nap Synthetic Fiber

Airless Spray -
 .017 to .019 Tip