



ProPaint® Flat
508XX

<p>Product Description:</p>	<p>Product Specifications:</p>						
<p>ProPaint Flat is a smooth flowing washable matte finish formulated for most wall surfaces in homes, apartments, commercial and public buildings. This versatile product provides high hiding and excellent application characteristics on new or previously painted surfaces.</p>	<p>Type: Vinyl Acrylic Latex Exposure: Interior Specular Gloss: 2 @ 60° ± 2 Volume Solids: 30.9 % ± 2 Solids by Weight: 50.7 % ± 2 Vehicle: 57.0 % ± 2 Pigment: 43.0 % ± 2 Dry Film Thickness: 1.4 mils Viscosity @ 77 °F: 108 KU ± 5 Maximum VOC: 100 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p>						
<p>Recommended Use:</p>	<p>Available Colors and Bases:</p> <table border="0"> <tr> <td>Super Hide White</td> <td>Stock</td> </tr> <tr> <td>Pastel</td> <td>Medium</td> </tr> <tr> <td>Deep</td> <td>Neutral</td> </tr> </table>	Super Hide White	Stock	Pastel	Medium	Deep	Neutral
Super Hide White	Stock						
Pastel	Medium						
Deep	Neutral						
<p>Plaster, sheetrock, wallboard, concrete, masonry block, wood, primed metal, primed galvanized metal, acoustical surfaces.</p>	<p>Available Package Sizes:</p> <table border="0"> <tr> <td>Gallon</td> <td>5 Gallon</td> </tr> </table> <p>(Weight Per Gallon: 11.7 lbs. ± .5 lb)</p>	Gallon	5 Gallon				
Gallon	5 Gallon						
<p>Application:</p>	<p>Drying Times:</p> <table border="0"> <tr> <td>To Touch:</td> <td>1 hrs.</td> </tr> <tr> <td>To Handle:</td> <td>4 hrs.</td> </tr> <tr> <td>To Recoat:</td> <td>2 hrs.</td> </tr> </table> <p>(@ 70-77 °F, 50% R.H.)</p>	To Touch:	1 hrs.	To Handle:	4 hrs.	To Recoat:	2 hrs.
To Touch:	1 hrs.						
To Handle:	4 hrs.						
To Recoat:	2 hrs.						
<p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. ProPaint Flat is self-priming over bare sheetrock, composition board, ceiling tile and concrete.</p> <p>New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper. Ferrous Metal, Galvanized Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer. Masonry Block - Apply one coat of ProPaint Block Filler 51500 if a denser surface is desired.</p>	<p>Surface Spread Rate:</p> <table border="0"> <tr> <td>Smooth:</td> <td>325-375 s.f./gal.</td> </tr> <tr> <td>Porous:</td> <td>250-300 s.f./gal.</td> </tr> </table> <p>(Spray Application is 50% of above)</p>	Smooth:	325-375 s.f./gal.	Porous:	250-300 s.f./gal.		
Smooth:	325-375 s.f./gal.						
Porous:	250-300 s.f./gal.						
<p>Architectural Specifications:</p>	<p>Tools and Equipment:</p> <p>Brush - Synthetic, Nylon or Polyester</p> <p>Roller - 3/8" Nap Synthetic Fiber</p> <p>Airless Spray - .017 to .019 Tip</p>						
<ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock: 2 coats ProPaint Flat 508XX ▪ Concrete, Non-Porous Masonry: 2 coats ProPaint Flat 508XX ▪ Porous Masonry and Block: 1 coat ProPaint Block Filler 51500 1 or 2 coats ProPaint Flat 508XX ▪ Ferrous Metal - Un-primed: 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150 1 or 2 coats ProPaint Flat 508XX ▪ Galvanized Metal: 1 coat Larcoloid Acrylic Latex Rust Inhibiting Metal Primer, White 51106, Gray 51108, Red 51107 1 or 2 coats ProPaint Flat 508XX ▪ Wood: 1 coat Prime Touch™ Professional Acrylic Latex Primer/Sealer 54500 1 or 2 coats ProPaint Flat 508XX ▪ Acoustical Tile: 2 coats ProPaint Flat 508XX 							
<p>Precautions:</p>							
<p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p>							
<p>Safety Information:</p>							
<p>Keep out of reach of children. Do not take internally. Close container after each use.</p>							