



2010 Super-Scrub® Ceramic Eggshell With Microban® Red Base

55196

Product Description:

2010 Super-Scrub Ceramic 100% Acrylic Waterborne Eggshell with Microban Red Base is a super premium eggshell finish designed to provide superior hiding power for some of the deep colors that typically require 5 to 6 coats*. It is also ideal as a primer under latex or oil finishes, both interior and exterior, where a sheen other than eggshell is desired.

See the detailed product description of Super Scrub Ceramic Eggshell with Microban on the 551XX specification sheet.

Recommended Use:

Plaster, sheetrock, wallboard, concrete, masonry block, wood, primed metal, galvanized metal, acoustical surfaces.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. 2010 Super-Scrub Ceramic 100% Acrylic Waterborne Eggshell with Microban Red Base is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

Since this product is designed as a base for a number of custom formulas to give them better hiding, 2010 Super Scrub Ceramic Eggshell with Microban Red Base 55196 is packaged in a 12 liq. oz. short-filled gallon to make room for additional colorant.*

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Ferrous Metal - Clean, then prime with Larcoloid® Rust Inhibiting Metal Primer

Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer.

Architectural Specifications:

- Plaster, Wallboard, Sheetrock:
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Concrete, Non-Porous Masonry:
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Porous Masonry and Block:
1 coat Mason-Cote® Block Filler 3751
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Ferrous Metal - Un-primed:
1 coat Larcoloid® Rust Inhibiting Metal Primer 21150
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Ferrous Metal - Primed, Galvanized Metal:
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Wood:
1 coat Prime Choice™ All Surface Acrylic Primer 50300
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196
- Acoustical Tile:
2 coats 2010 Super-Scrub Ceramic Eggshell with Microban Red Base 55196

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

*Here is a listing of 10 PERFECT PALETTE®** (and 5 HISTORIC) colors whose formulations can have their hiding vastly enhanced by the use of this Red Base No. 55196:

PERFECT PALETTE Colors-
Cherry Bomb DEA105; Deep Crimson DEA152; Glitzy Red DEA153; Hot Jazz DEA107; Red Contrast DEA106; Red Icon DEA104; Red Ink DEA151; Red Revival DEA154; Scarlet Past DEA150 and Striking Red DEA103

HISTORIC Colors-
Codman Claret; Redrock Canyon; Richardson Brick; Shaker Red and Stagecoach

Contact your Dealer or our Customer Service Department if you would like to obtain these formulas.

**The Perfect Palette Color System and all rights therein is property of Dunn-Edwards Corporation, used under license by California Products Corporation.

California Paints • 150 Dascomb Rd. • Andover, MA • 01810 • www.californiapaints.com • 800-225-1141

Product Specifications:

Type: 100% Acrylic Latex
Exposure: Interior or Exterior
Specular Gloss: 12 @ 60° ± 2
Volume Solids: 32.4 % ± 2
Solids by Weight: 40.0 % ± 2
Vehicle: 86.8 % ± 2
Pigment: 13.2 % ± 2
Dry Film Thickness: 2 mils
Viscosity @ 77 °F: 97 KU ± 5
Maximum VOC: 150 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

Red

Available Package Sizes:

Quart Gallon

(Weight Per Gallon: 9.5 lbs. ± .5 lb)

Drying Times:

To Touch: 1 hrs.
To Handle: 8 hrs.
To Recoat: 4 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 350-400 s.f./gal.
Porous: 250-300 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.017 to .019 Tip