



ProPaint® Block Filler

51500

<p>Product Description: This alkali resistant block filler is formulated to fill pores and small voids in masonry and light aggregate block. This ready-mixed interior vinyl acrylic block filler eliminates pin holing and produces a uniform surface texture ready for finish coating.</p>	<p>Product Specifications: Type: Vinyl Acrylic Latex Exposure: Interior Specular Gloss: 2 @ 60° ± 2 Volume Solids: 46.7 % ± 2 Solids by Weight: 66.3 % ± 2 Vehicle: 44.0 % ± 2 Pigment: 56.0 % ± 2 Dry Film Thickness: 5 mils Viscosity @ 77 °F: 109 KU ± 5 Maximum VOC: 100 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p>
<p>Recommended Use: Concrete Block, Porous Masonry and Concrete</p>	<p>Available Colors and Bases: White</p>
<p>Application: WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424- LEAD (5323) or log on to www.epa.gov/lead. Masonry block should be "bricked down" so that all concrete nibs and projections are removed from the surface. Loose mortar, dirt, dust, grease and oil must also be removed before applying ProPaint Block Filler. Large concrete voids or cracks should be patched with an appropriate oilfree patching material before painting. ProPaint Block Filler is supplied ready-to-use but can be thinned sparingly with water if necessary. It can be applied by brush, roller or spray. Brush - Use a synthetic nylon or polyester brush and apply material generously to the surface. Work the Filler into the masonry until all voids and hairline cracks are filled. Material should be finished brushed in one direction to create an even appearance. Roller - Use a synthetic or lambs wool 3/8" - 3/4" nap roller cover. Work material into block and finish roll horizontally. Spray - ProPaint Block Filler is silica free and can be successfully sprayed without doing physical damage to spray equipment. Heavy duty airless units using a .021 to .028 tip are ideal for large scale block filler applications.</p>	<p>Available Package Sizes: 5 Gallon (Weight Per Gallon: 13.2 lbs. ± .5 lb)</p>
<p>Architectural Specifications: <ul style="list-style-type: none"> • Porous Masonry, Block, Concrete: 1 coat ProPaint Block Filler 51500 1 or 2 coats California® Latex, Alkyd or Oil-modified Urethane in desired finish. </p>	<p>Drying Times: To Touch: 4 hrs. To Handle: 8 hrs. To Recoat: 4 hrs. (@ 70-77 °F, 50% R.H.)</p>
<p>Precautions: Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50 °F or when drying conditions are poor. Keep from freezing. Do not use under catalyzed epoxies, epoxy polyesters or aliphatic urethanes.</p>	<p>Surface Spread Rate: Smooth: N/A s.f./gal. Porous: 100-150 s.f./gal. (Spray Application is 50% of above)</p>
<p>Safety Information: Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p>Tools and Equipment: Brush - Synthetic, Nylon or Polyester Roller - 3/8" -3/4" Nap Synthetic Fiber Airless Spray - .021 to .028</p>