

Product Description:

Wipe-Out 100% Acrylic Latex Stain Block 52500 is a quick drying, high performance 100% acrylic latex stain blocking primer that provides exceptional adhesion and stain blocking properties. This environmentally friendly product may be used interior or exterior to block most bleeding type stains, seal porous surfaces and provide adhesion to hard and glossy surfaces.

Recommended Use:

Wallboard, Plaster, Sheetrock, Concrete, Masonry, Wood, Aluminum, Galvanized Metal, Plastic Laminates, Vinyl Wall Coverings, Previously Painted Surfaces

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be primed must be clean, dry, and free of grease, oil, wax, rust, loose paint, mildew or any surface contaminants. Wash glue size off plaster or other surfaces from which wallpaper has been removed.

Do not apply over calcimine, casein or other water soluble paints. Fill nicks, holes and voids with appropriate patching material, sand smooth and remove dust.

New plaster and masonry surfaces must be fully cured before priming.

Sanding is not required for properly and thoroughly cleaned hard or glossy surfaces, but abrasion of the surface will increase adhesion of this product.

Do not sand plaster until after the surface is primed.

Tape joints on sheetrock should be sanded smooth, with care being exercised not to abrade the surrounding paper backing.

Stains: Wipe-Out 100% Acrylic Stain Block hides well to seal many common stains such as crayon, graffiti, greasy spots, water stains, rust, smoke stains, cedar and redwood bleed. Before priming stained areas, remove as much of the stain as possible by washing, sanding or scraping. Some stains may require two coats. If an active stain discolors this primer, apply the finish coat to a small area to see if the stain is "locked" into the primer. If not, re-prime.

Plasticizers must be thoroughly removed from vinyl wall coverings with mineral spirits, proper ventilation and a clean cloth that is changed frequently.

Architectural Specifications:

- Plaster, Wallboard, Sheetrock, Concrete, Masonry, Galvanized Metal Wood, Aluminum:
 - 1 coat Wipe-Out 100% Acrylic Stain Block 52500
 - 1 or 2 coats any California® Latex, Alkyd or Urethane in desired finish.

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Difficult stains may require the use of Wipe-Out® or Wipe-Out Low Odor® Stain Block.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: 100% Acrylic Latex
Exposure: Interior or Exterior
Specular Gloss: 15 @ 60° ± 5
Volume Solids: 33.4% ±2
Solids by Weight: 46.9% ±2
Vehicle: 76.1% ±2
Pigment: 23.9% ±2
Dry Film Thickness: 1.5 mils
Viscosity @ 77 °F: 95KU ± 5
Maximum VOC: 150 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White

Available Package Sizes:

Quart Gallon 5 Gallon

(Weight Per Gallon: 10.5 lbs. ± .5 lb)

Drying Times:

To Touch: .5 hrs.
To Handle: 4 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 350-400 s.f./gal.
Porous: 200-250 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.017 to .019 Tip