



# ENVIROTECH Zero VOC Interior Latex Primer-Sealer Enamel

**Undercoater 100% Acrylic Latex 64600**

<p><b>Product Description:</b></p> <p>ENVIROTECH Zero VOC Primer is an environmentally preferred, quality interior Primer-Sealer Enamel Undercoater. It is an ideal undercoater for new or previously painted surfaces. With essentially no odor during and after application, rooms and offices painted with ENVIROTECH Zero VOC can be occupied right away without a compromise to healthy indoor air quality. Fast-drying ENVIROTECH Primer seals surfaces for uniform finish coat application, texture, gloss and color.</p>	<p><b>Product Specifications:</b></p> <p><b>Type:</b> 100% Acrylic Latex  <b>Exposure:</b> Interior  <b>Specular Gloss:</b> 4 @ 60° ± 2  <b>Volume Solids:</b> 41.8 % ± 2  <b>Solids by Weight:</b> 56.5 % ± 2  <b>Vehicle:</b> 62.4 % ± 2  <b>Pigment:</b> 34.7 % ± 2  <b>Dry Film Thickness:</b> 2.3 mils  <b>Viscosity @ 77 °F:</b> 100 KU ± 5  <b>Maximum VOC:</b> Calc. 0g/liter  <b>Flash Pt °F:</b> Non-combustible  <b>Thinner:</b> Water  <b>Clean Up:</b> Soap &amp; Water</p>
<p><b>Recommended Use:</b></p> <p>Plaster, Sheetrock, Wallboard, Concrete, Masonry block, Wood, previously finished surfaces.</p>	<p><b>Available Colors and Bases:</b></p> <p>White</p>
<p><b>Application:</b></p> <p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound.</p> <p>New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.</p> <p>Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.</p> <p>Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer</p> <p>Masonry Block - Apply one coat of Mason-Cote® Block Filler 3751 if a denser surface is desired.</p>	<p><b>Available Package Sizes:</b></p> <p>Gallon 5 Gallon</p> <p>(Weight Per Gallon: 11.2 lbs. ± .5 lb)</p>
<p><b>Architectural Specifications:</b></p> <ul style="list-style-type: none"> <li>▪ Plaster, Wallboard, Sheetrock:             <ul style="list-style-type: none"> <li>1 coat ENVIROTECH Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 64600</li> <li>1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote® Polyamide Epoxy 1200 Series</li> </ul> </li> <li>▪ Concrete, Non-Porous Masonry:             <ul style="list-style-type: none"> <li>1 coat ENVIROTECH Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 64600</li> <li>1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote® Polyamide Epoxy 1200 Series</li> </ul> </li> <li>▪ Wood:             <ul style="list-style-type: none"> <li>1 coat ENVIROTECH Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 64600</li> <li>1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote® Polyamide Epoxy 1200 Series</li> </ul> </li> </ul>	<p><b>Drying Times:</b></p> <p><b>To Touch:</b> 1 hrs.  <b>To Handle:</b> 4 hrs.  <b>To Recoat:</b> 2 hrs.</p> <p>(@ 70-77 °F, 50% R.H.)</p>
<p><b>Precautions:</b></p> <p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p>	<p><b>Surface Spread Rate:</b></p> <p><b>Smooth:</b> 400-450 s.f./gal.  <b>Porous:</b> 350-400 s.f./gal.</p> <p>(Spray Application is 50% of above)</p>
<p><b>Safety Information:</b></p> <p>Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p><b>Tools and Equipment:</b></p> <p><b>Brush -</b> Synthetic, Nylon or Polyester</p> <p><b>Roller -</b> 3/8" Nap Synthetic Fiber</p> <p><b>Airless Spray -</b> .017 to .019 Tip</p>