



flawless ELEMENTS™ Zero VOC Interior Latex Primer-Sealer Enamel Undercoater 100% Acrylic Latex with Microban® 74600

| Product Description: | Product Specifications: |
|---|--|
| <p>flawless ELEMENTS™ Zero VOC Primer is an environmentally preferred, premium quality interior Primer-Sealer Enamel Undercoater with Microban® antimicrobial protection. It is the perfect undercoater for new or previously painted surfaces. With essentially no odor during and after application, rooms and offices painted with flawless ELEMENTS Zero VOC can be occupied right away without a compromise to healthy indoor air quality. Mildew resistant and fast-drying flawless ELEMENTS Primer seals surfaces for uniform finish coat application, texture, gloss and color.</p> | <p>Type: 100% Acrylic Latex Exposure: Interior Specular Gloss: 4 @ 60° ± 2 Volume Solids: 42.0 % ± 2 Solids by Weight: 57.3 % ± 2 Vehicle: 64.5 % ± 2 Pigment: 35.5 % ± 2 Dry Film Thickness: 2.4 mils Viscosity @ 77 °F: 100 KU ± 5 Maximum VOC: Calc. 0g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p> |
| Recommended Use: | |
| <p>Plaster, Sheetrock, Wallboard, Concrete, Masonry block, Wood, previously finished surfaces.</p> | |
| Application: | |
| <p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound.</p> <p>New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper. Wood - Seal knots and stains with Wipe-Out® , Wipe-Out Low Odor or Wipe-Out 100% Acrylic Stain Block Masonry Block - Apply one coat of Mason-Cote® Block Filler if a denser surface is desired.</p> | <p>Available Colors and Bases: White</p> |
| Architectural Specifications: | |
| <ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock: 1 coat flawless ELEMENTS Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 74600 1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote ® Polyamide Epoxy 1200 Series ▪ Concrete, Non-Porous Masonry: 1 coat flawless ELEMENTS Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 74600 1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote ® Polyamide Epoxy 1200 Series ▪ Wood: 1 coat flawless ELEMENTS Zero VOC Interior 100% Acrylic Latex Latex Primer-Sealer 74600 1 or 2 coats California Latex, Alkyd, Oil-Modified Polyurethane, Tile-Cote ® Polyamide Epoxy 1200 Series | <p>Available Package Sizes: Quart Gallon 2 Gallon 5 Gallon (Weight Per Gallon: 11.3 lbs. ± .5 lb)</p> |
| Precautions: | |
| <p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50 °F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p> | <p>Drying Times: To Touch: 1 hrs. To Handle: 4 hrs. To Recoat: 2 hrs. (@ 70-77 °F, 50% R.H.)</p> |
| Safety Information: | |
| <p>Keep out of reach of children. Do not take internally. Close container after each use.</p> | <p>Surface Spread Rate: Smooth: 400-450 s.f./gal. Porous: 350-400 s.f./gal. (Spray Application is 50% of above)</p> |
| | <p>Tools and Equipment: Brush - Synthetic, Nylon or Polyester Roller - 3/8" Nap Synthetic Fiber Airless Spray - .017 to .019 Tip</p> |