



Rust-Stop® DTM 100% Acrylic Latex Semi-Gloss 10XX

Product Description:

A rust inhibiting 100% acrylic latex paint for use on ferrous metal, galvanized metal and other surfaces exposed to general industrial and atmospheric conditions. Rust-Stop has good aliphatic solvent and water resistance and excellent resistance to most alkalis, detergents and mild acids. This acrylic latex metal paint does not contain the flammable solvents contained in other rust inhibiting paints, has low odor and fast recoatability.

Recommended Use:

Ideal for painting both new and previously painted roof decks, metal paneling, corrugated metal siding, storage tank exteriors, miscellaneous iron, bar joists and structural steel. Rust-Stop also provides excellent adhesion to galvanized ductwork and enclosures and for adjacent surfaces of wood and concrete.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Remove all oil, grease, dirt, mill scale, loose or scaling paint and other foreign matter.

FERROUS METAL — "Power Tool" clean (SSPC-SP3) back to sound substrate. ALUMINUM — Unfinished aluminum should be wiped with mineral spirits on a clean rag to remove oil. Aluminum oxide on old weathered aluminum should be removed with steel wool and mineral spirits. GALVANIZED METAL — Oil residue should be wiped off with mineral spirits on a clean rag. PREVIOUSLY PAINTED SURFACES — Prepare ruptured or scratched surfaces as for unfinished metal, spot prime bare metal as conditions dictate.

Architectural Specifications:

Precautions:

Surface and air temperature must be 50°F or above during application and drying time. Do not recoat with coatings using aromatic or other strong solvents. Do not intermix with solvent base primers or finishes.

Safety Information:

CONTAINS:NON VOLATILE ACRYLIC RESINS CAUTION! KEEP OUT OF THE REACH OF CHILDREN DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN FOR INDUSTRY USE ONLY

Product Specifications:

Type: 100% Acrylic Latex Exposure: Interior or Exterior Specular Gloss: 35@ 60° ± 5 Volume Solids: 34.4 % ±2 Solids by Weight: 48.3 % ±2 Vehicle: 75.4 % ±2 Pigment: 24.6 % ±2 Dry Film Thickness: 1.4 mils Viscosity @ 77 °F: 80 KU ±5 Maximum VOC: 340 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water

Available Colors and Bases:

White Black Bronzestone Pastel Medium Deep Ultra Deep Neutral

Available Package Sizes:

Quart Gallon 5 Gallon

(Weight Per Gallon: 10.7 lbs. ± .5 lb)

Drying Times:

To Touch: 2 hrs. To Handle: 24 hrs. To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 375-425 s.f./gal. Porous: 300-350 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush - Synthetic, Nylon or Polyester

Roller - 3/8" Nap Synthetic Fiber

Airless Spray - Airless .017 - .019 Tip