



Skid-Grip® Urethane Floor Enamel
2231,6

Product Description:

A heavy duty oil modified gloss polyurethane enamel, Skid Grip Urethane Enamel is formulated for the maximum wearability available in a one-package coating for heavy use exposures requiring a skid resistant finish. Skid Grip provides a hard mirror-like finish which will withstand detergents, dirt, mud, grease, grime and abrasion.

Recommended Use:

Ideal for factory, school and institutional applications subject to heavy use. Designed for use on concrete, metal, wood, wallboard, or masonry block. May be used wherever a heavy duty abrasion and skid resistant enamel finish is required.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

MIXING — Stir with a lifting action to fully incorporate pigments.

THINNING — Material is supplied at application consistency but can be thinned if necessary by adding small amounts of mineral spirits for brushing or rolling. Use mineral spirits to clean equipment after use.

Architectural Specifications:

Precautions:

Do not use in areas where heavy-duty forklift traffic is expected. Steel troweled smooth concrete or concrete with a hardener or curing membrane may require mechanical abrasion to obtain proper adhesion. Do not apply Skid-Grip Floor Coating to concrete floors laid below ground level or laid directly on moist ground without acid etching.

Do not apply to exterior surfaces in damp or foggy weather or when rain is imminent. Air and surface temperatures should be over 50°F during application and drying period. Inadequate ventilation will retard drying time. Do not mix with water, linseed oil, latex or other finishes. Do not use for immersion service. Skid-Grip Floor Coating is not recommended over asphalt or vinyl asphalt tile, quarry tile or ceramic tile.

CAUTION: All floor enamels are more slippery when the surface becomes wet or contaminated by dirt, oils, food or beverage residues or other debris. To attain the best possible skid resistance, coated areas must be kept dry, properly cleaned and maintained.

Safety Information:

CONTAINS: PETROLEUM DISTILLATE

Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician. For skin, wash thoroughly with soap and water. If swallowed, call a physician immediately. Never give anything by mouth to an unconscious person. Remove contaminated clothing, including shoes. Wash clothing before re-use. Discard contaminated shoes.

NOTICE: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRY USE ONLY

Product Specifications:

Type: Oil Modified Urethane
Exposure: Interior or Exterior
Specular Gloss: NA@ 60° ±
Volume Solids: 58.1 % ±2
Solids by Weight: 72.5 % ±2
Vehicle: 69.5 % ±2
Pigment: 30.5 % ±2
Dry Film Thickness: 3.3 mils
Viscosity @ 77 °F: NA KU ±5
Maximum VOC: 340 g/liter
Flash Pt °F: 103
Thinner: Mineral Spirits
Clean Up: Mineral Spirits

Available Colors and Bases:

Battleship Gray
Coast Guard Gray

Available Package Sizes:

Gallon

(Weight Per Gallon: 9.2 lbs. ± .5 lb)

Drying Times:

To Touch: 4-6 hrs.
To Handle: 24 hrs.
To Recoat: 16 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 250-300 s.f./gal.
Porous: s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Natural Bristle

Roller -
3/8" Nap Synthetic Fiber