



Mason-Cote® 100% Acrylic Latex Block Filler

3751

Product Description:

Mason-Cote Block Filler is a high quality exterior acrylic block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before topcoating. This product contains mineral type fillers and fine silica aggregates which fill voids and prevent seepage from driving rains and snow. This 100% acrylic block filler is easy to apply, alkali resistant and provides a uniform surface capable of receiving all types of finish coats. Mason-Cote Block Filler is not water sensitive after application and its inherent flexibility gives it the finest characteristics available in an exterior block filler, far superior to cementitious and PVA block fillers.

Recommended Use:

Masonry block, concrete, brick, stone

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Nibs and mortar joints should be "bricked down" to remove all protrusions and mortar splatters. All dirt, grease, oil and other contaminants should be removed by brushing or solvent washing. Mason-Cote Block Filler is supplied ready to use and can be applied by brush or roller. Spray application is not recommended because the silica content is abrasive to spray equipment.

Thin sparingly with water, if thinning is necessary. Maximum block filling qualities are achieved with use of a roller (3/8" in nap or longer). Mason-Cote Block Filler should be applied full body vertically and cross hatched horizontally to remove all roller ridges and unevenness in the block filler. Brushing should be done with a short stubby brush, working the material well into the pinholes, pores and voids. Material should be applied in horizontal sections with the block mortar lines serving as a guide.

Architectural Specifications:

- CONCRETE BLOCK, MASONRY
- 1 coat Mason-Cote Block Filler
- 1 or 2 coats California Acrylic Latex, Alkyd, Urethane or Epoxy

Precautions:

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: 100% Acrylic Latex
Exposure: Interior or Exterior
Specular Gloss: 2 @ 60° ± 2
Volume Solids: 47.6 % ± 2
Solids by Weight: 66.9 % ± 2
Vehicle: 44.1 % ± 2
Pigment: 55.9 % ± 2
Dry Film Thickness: 3.8 mils
Viscosity @ 77 °F: 112 KU ± 5
Maximum VOC: 100 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White

Available Package Sizes:

5 Gallon

(Weight Per Gallon: 13.2 lbs. ± .5 lb)

Drying Times:

To Touch: 4-8 hrs.
To Handle: 16 hrs.
To Recoat: 24 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: s.f./gal.
Porous: 190-210 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
Not Recommended