



**Dryfall Economy Latex Flat
37XX**

Product Description:

Ready to use odorless vinyl acrylic flat latex paint formulated for airless spray application on interior surfaces. Economy Spray Paint may be used on wood, gypsum board, plaster, concrete, masonry block and completely primed ferrous metal. This latex spray paint can be used as dry fall paints on ceilings 16 feet or higher when the relative humidity is less than 70%.

Recommended Use:

Ideal for wall and ceiling surfaces in industrial plants, commercial buildings, warehouses, public institutions, schools and churches.

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces must be clean, dry and free of dirt, dust and other contaminants.

CONCRETE — Remove nibs and mortar splatter.

FERROUS METAL — Must be completely primed with a rust inhibiting primer.

GYPSON BOARD, PLASTER, WOOD — Fill cracks and voids with oil free patching compounds.

PREVIOUSLY PAINTED SURFACES — These products are compatible with old finishes except water soluble paints such as calcimine or casein. Test questionable areas with a sponge and water. If water softens the surface, the old finish will have to be removed before finishing with latex.

Architectural Specifications:

PRIMERS & FINISHES: Recommended compatible primers should always be used for specified surfaces.

- **WOOD, CONCRETE, GYPSUM BOARD, PLASTER, MASONRY BOARD**
2 coats Economy Spray Flat
- **FERROUS METAL** — Unprimed
1 coat Combatit® — Red Oxide Shop Primer #1050
1 coat Economy Spray Flat
- **PREVIOUSLY PAINTED SURFACES**
1 coat Economy Spray Flat

Precautions:

High humidity or low temperatures will retard drying time. Do not use as a primer for other paints. Air and surface temperatures should be 50°F or higher during application and drying time. Do not use over unprimed ferrous metal.

Safety Information:

CONTAINS: NON VOLATILE VINYL-ACRYLIC RESINS
CAUTION!: KEEP OUT OF THE REACH OF CHILDREN
DO NOT TAKE INTERNALLY.
CLOSE CONTAINER AFTER EACH USE.
KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY

Product Specifications:

Type: Vinyl Acrylic Latex
Exposure: Interior
Specular Gloss: 4 @ 60° ±2
Volume Solids: 32.3 % ±2
Solids by Weight: 52.8 % ±2
Vehicle: 53.8 % ±2
Pigment: 46.2 % ±2
Dry Film Thickness: 2.5 mils
Viscosity @ 77 °F: 103 KU ±5
Maximum VOC: 100 g/liter
Flash Pt °F: Non combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

White Black

Available Package Sizes:

5 Gallon

(Weight Per Gallon: 12.0 lbs. ± .5 lb)

Drying Times:

To Touch: 2 hrs.
To Handle: 4 hrs.
To Recoat: 2 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 175-225 s.f./gal.
Porous: 130-160 s.f./gal.
 (Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester

Roller -
3/8" Nap Synthetic Fiber

Airless Spray -
.015 to .018 Tip / 40-60° angles