



**Larcoloid® 100% Acrylic Latex Gloss Enamel
511XX**

<p>Product Description:</p>	<p>Product Specifications:</p>
<p>This smooth flowing, non-toxic, 100% acrylic latex enamel provides a quick dry gloss finish for most general maintenance requirements. It provides superior color retention and moisture resistance when used exterior and is rust inhibiting when applied in the proper system.</p>	<p>Type: 100% Acrylic Latex Exposure: Interior or Exterior Specular Gloss: 65 @ 60° ± 5 Volume Solids: 35.4 % ± 2 Solids by Weight: 49.0 % ± 2 Vehicle: 76.3 % ± 2 Pigment: 23.7 % ± 2 Dry Film Thickness: 1.5 mils Viscosity @ 77 °F: 85 KU ± 5 Maximum VOC: 250 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p>
<p>Recommended Use:</p> <p>Wood, plaster, concrete, masonry block, wallboard, primed metal.</p>	<p>Available Colors and Bases:</p> <p>White 11 Stock Pastel Medium Deep Ultra Deep Neutral</p>
<p>Application:</p> <p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. Larcoloid Acrylic is self-priming over bare sheetrock, composition board, ceiling tile and concrete.</p> <p>New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper. Ferrous Metal - Clean, then prime with Larcoloid ® Rust Inhibiting Metal Primer Wood - Seal knots and stains with Prime Choice™ Low Odor Oil Base Primer Sealer or Prime Choice™ 100% Acrylic Universal Primer Masonry Block - Apply one coat of Mason-Cote® Block Filler 3751 if a denser surface is desired. Previously Painted Surfaces - Wash, sand or dust to obtain a paintable surface. Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.</p>	<p>Available Package Sizes:</p> <p>Pint Quart Gallon</p> <p>(Weight Per Gallon: 10.6 lbs. ± .5 lb)</p>
<p>Architectural Specifications:</p> <ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock, Concrete, Non-Porous Masonry: <ul style="list-style-type: none"> 1 Coat Prime Choice™ All Surface Acrylic Primer 50300 1 or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX ▪ Porous Masonry and Block: <ul style="list-style-type: none"> 1 coat Mason-Cote® Block Filler 3751 1 or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX ▪ Ferrous Metal - Unprimed: <ul style="list-style-type: none"> 1 coat Larcoloid Rust Inhibiting Metal Primer Latex or Alkyd 1 or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX ▪ Ferrous Metal - Primed - Galvanized Metal: <ul style="list-style-type: none"> 1 or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX ▪ Wood: <ul style="list-style-type: none"> 1 coat Prime Choice™ All Surface Acrylic Primer 50300 1 or 2 coats Larcoloid 100% Acrylic Gloss Enamel 511XX 	<p>Drying Times:</p> <p>To Touch: 1 hrs. To Handle: 24 hrs. To Recoat: 2 hrs. (@ 70-77 °F, 50% R.H.)</p>
<p>Precautions:</p> <p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Do not use in place of House Paint. Remove all mildew before application. For maximum rust inhibiting requirements prime bare ferrous metal with California High Performance Industrial Prime-Line Metal Primer.</p>	<p>Surface Spread Rate:</p> <p>Smooth: 350-400 s.f./gal. Porous: 275-325 s.f./gal. (Spray Application is 50% of above)</p>
<p>Safety Information:</p> <p>Keep out of reach of children. Do not take internally. Close container after each use.</p>	<p>Tools and Equipment:</p> <p>Brush - Synthetic, Nylon or Polyester</p> <p>Roller - 3/8" Nap Synthetic Fiber</p> <p>Airless Spray - .017 to .019 Tip</p>