



Lacrylic® Clear Anti-Graffiti / Waterproofing Coating

7110

Product Description:

This crystal clear multi-purpose acrylic sealer provides non-yellowing protection to a large variety of surfaces. LACRYLIC will seal both interior and exterior poured concrete wall and floor surfaces, to prevent both water penetration and surface dusting. This material can be topcoated with itself to provide an abrasion resistant clear coating, or topcoated with pigmented alkyd or urethane. Flagstone, terra cotta and slate can be sealed and finished with two coats of LACRYLIC. LACRYLIC seals common red brick and prevents oxide bleed-through on finish coats of paint. LACRYLIC will also seal old unfinished stucco to prevent loss of adhesion of latex finish coats. LACRYLIC is an excellent sacrificial anti-graffiti coating.

Recommended Use:

Masonry, Stucco, Flagstone, Brick, Concrete Floors

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead. Remove all surface contaminants including grease, oil, rust, stains, dirt, dust, wax and mortar splatter. New concrete must cure for a minimum of 28 days prior to application of Lacrylic. Lacrylic is supplied at proper application consistency and generally requires no thinning. Material can be applied successfully by brush, roller or airless spray. Apply full-body working the material into the pores of the surface. Clean up sealer spatters and equipment immediately after use with #2308 thinner.

Architectural Specifications:

- Concrete Floors
2 coats Lacrylic Clear Anti-graffiti / Waterproofing Coating
Patio Flagstone, Terra Cotta
2 coats Lacrylic Clear Anti-graffiti / Waterproofing Coating
Brick - Painted: Common, Red Clay Type (or soot stained)
1 coat Lacrylic Clear Anti-graffiti / Waterproofing Coating
2 coats California® Acrylic Latex
Wood (& Plywood): Low Gloss Stain Proof Finish
2 coats Lacrylic Clear Anti-graffiti / Waterproofing Coating

Precautions:

Do not mix with water or other type paints. Do not apply below 40°F or apply to a damp surface. Not recommended as a sealer on glazed, quarry or other ceramic type tiles. Steel troweled concrete must be acid etched prior to application of Lacrylic to ensure adhesion to the concrete. Steel troweled smooth concrete with a curing membrane or hardener may require abrasion to obtain proper adhesion.

Safety Information:

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE. HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM, CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES NOSE, THROAT, EYE AND SKIN IRRITATION. CONTAINS PETROLEUM DISTILLATE. Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Do not transfer contents to unlabeled bottles or other containers. Close container after each use. Avoid contact with skin. FIRST AID: If swallowed, CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious person. USE WITH ADEQUATE VENTILATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. FOR INDUSTRY USE ONLY KEEP OUT OF REACH OF CHILDREN

Product Specifications:

Type: Solvent Acrylic
Exposure: Interior or Exterior
Specular Gloss: NA@ 60° ±
Volume Solids: 14.9 % ±2
Solids by Weight: 19.1 % ±2
Vehicle: 100 % ±2
Pigment: % ±2
Dry Film Thickness: 1.2 mils
Viscosity @ 77 °F: NA KU ±5
Maximum VOC: 600 g/liter
Flash Pt °F: 108
Thinner: 2308
Clean Up: Xylol

Available Colors and Bases:

Clartone

Available Package Sizes:

Gallon 5 Gallon

(Weight Per Gallon: 7.8 lbs. ± .5 lb)

Drying Times:

To Touch: .5 hrs.
To Handle: 1 hrs.
To Recoat: 1 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 150-175 s.f./gal.
Porous: 100-125 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

- Brush - Natural Bristle
Roller - 3/8" Nap Synthetic Fiber
Airless Spray - .011 to .013 Tip