

# Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

# **ICP Construction**

Version No: **2.3**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **05/03/2018**Print Date: **05/15/2018**S.GHS.USA.EN

# **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	Ultra 2010 Exterior Semi Gloss Pastel Base - 40291			
Synonyms	Not Available			
Other means of identification	Not Available			

#### Recommended use of the chemical and restrictions on use

# Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction					
Address	Dascomb Road MA 01810 United States					
Telephone	3-9980					
Fax	lot Available					
Website	https://www.icp-construction.com/					
Email	Not Available					

## **Emergency phone number**

3, .	
Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

# **SECTION 2 HAZARD(S) IDENTIFICATION**

# Classification of the substance or mixture

# NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Carcinogenicity Category 1B, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3

# Label elements

Hazard pictogram(s)



SIGNAL WORD

DANGER

## Hazard statement(s)

H350	May cause cancer.		
H412	Harmful to aquatic life with long lasting effects.		

# Hazard(s) not otherwise specified

Not Applicable

Chemwatch: 9-528015 Page 2 of 9 Issue Date: 05/03/2018 Version No: 2.3 Print Date: 05/15/2018

# Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. Precautionary statement(s) Prevention P201 Obtain special instructions before use. P281 Use personal protective equipment as required. Precautionary statement(s) Response Precautionary statement(s) Storage P405 Store locked up.

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

P501

#### Substances

See section below for composition of Mixtures

Precautionary statement(s) Disposal

# Mixtures

CAS No	[weight] Name		
57-55-6	1-5	propylene glycol	
1317-70-0	10-20	titanium dioxide (anatase)	
21645-51-2	0-5	aluminium hydroxide	
64742-99-0	<1	residual oils, oxidised	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Dispose of contents/container in accordance with local regulations.

# **SECTION 4 FIRST-AID MEASURES**

# Description of first aid measures

2001.					
Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.				
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.				
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>				
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>				

# Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Chemwatch: 9-528015 Page 3 of 9

Version No: 2.3

#### Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Issue Date: 05/03/2018 Print Date: 05/15/2018

Treat symptomatically.

for diuron:

- Symptomatic and supportive action is indicated.
- Methaemoglobinaemia is possible
- if compound is hydrolysed in vivo to aniline.
- Methaemoglobinaemia causes cyanosis. Reversion of methaemoglobin to haemoglobin is spontaneous after removal from exposure, so moderate degrees of cyanosis need be treated only by supportive measures such as bed rest and oxygen inhalation.
- F Thorough cleansing of the entire contaminated area of the body, including the scalp and nails is of the utmost importance.

for irritant gas exposures:

- the presence of the agent when it is inhaled is evanescent (of short duration) and therefore, cannot be washed away or otherwise removed
- retail blood gases are of primary importance to aid in determination of the extent of damage. Never discharge a patient significantly exposed to an irritant gas without obtaining an arterial blood
- ▶ supportive measures include suctioning (intubation may be required), volume cycle ventilator support (positive and expiratory pressure (PEEP), steroids and antibiotics, after a culture is taken
- If the eves are involved, an ophthalmologic consultation is recommended

Occupational Medicine: Third Edition: Zenz. Dickerson, Horvath 1994 Pub: Mosby

For acute or short term repeated exposures to ammonia and its solutions:

- Mild to moderate inhalation exposures produce headache, cough, bronchospasm, nausea, vomiting, pharyngeal and retrosternal pain and conjunctivitis. Severe inhalation produces laryngospasm, signs of upper airway obstruction (stridor, hoarseness, difficulty in speaking) and, in excessively, high doses, pulmonary oedema.
- Warm humidified air may soothe bronchial irritation.
- Test all patients with conjunctival irritation for corneal abrasion (fluorescein stain, slit lamp exam)
- ▶ Dyspneic patients should receive a chest X-ray and arterial blood gases to detect pulmonary oedema.

#### **SECTION 5 FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

- ▶ Dry chemical powder.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Special protective equipment and precautions for fire-fighters		
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> </ul>	

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> </ul>
Fire/Explosion Hazard	Combustible.     Slight fire hazard when exposed to heat or flame. Combustion products include: , carbon dioxide (CO2) , other pyrolysis products typical of burning organic material. May emit poisonous fumes.
	May emit corrosive fumes.

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Mothade and material for containment and cleaning up

methods and material for containment and cleaning up				
Minor Spills  ► Remove all ignition sources.  ► Clean up all spills immediately.				
Major Spills  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.				

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 HANDLING AND STORAGE**

#### Dunnantiana fan aafa bandlina

<ul> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ DO NOT allow clothing wet with material to stay in contact with skin</li> </ul>				
Other information  Store in original containers.  Keep containers securely sealed.				

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>

Chemwatch: 9-528015 Page 4 of 9

Version No: 2.3

#### Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Issue Date: **05/03/2018**Print Date: **05/15/2018** 

# Storage incompatibility

Titanium dioxide

- ► reacts with strong acids, strong oxidisers
- reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures these reactions involves reduction of the oxide and are accompanied by incandescence
- ▶ dust or powders can ignite and then explode in a carbon dioxide atmosphere
- ► Avoid reaction with oxidising agents

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Control parameters**

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide (anatase)	Rutile, Titanium oxide, Titanium peroxide	Not Available	Not Available	Not Available	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	titanium dioxide (anatase)	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	titanium dioxide (anatase)	Titanium dioxide: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	aluminium hydroxide	Synonyms vary depending upon the specific aluminum compound.	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	aluminium hydroxide	Synonyms vary depending upon the specific aluminum compound.	2 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	aluminium hydroxide	Aluminum metal and insoluble compounds	1 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium hydroxide	Particulates not otherwise regulated (PNOR): Total dust	15 mg/m3	Not Available	Not Available	(f) All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the Particulates Not Otherwise Regulated (PNOR) limit which is the same as the inert or nuisance dust limit of Table Z-3.

# EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
titanium dioxide (anatase)	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3
aluminium hydroxide	Aluminum hydroxide	8.7 mg/m3	73 mg/m3	440 mg/m3

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
titanium dioxide (anatase)	5000 mg/m3	Not Available
aluminium hydroxide	Not Available	Not Available
residual oils, oxidised	Not Available	Not Available

## **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

CARE: Explosive vapour air mixtures may be present on opening vessels which have contained liquid ammonia. Fatalities have occurred

# Personal protection







# Eye and face protection

- ► Safety glasses with side shields.
- Chemical goggles

# Skin protection

# See Hand protection below

# Hands/feet protection

- ► Wear chemical protective gloves, e.g. PVC.
- ► Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

# Body protection

# See Other protection below

## Other protection

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- ► Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.

#### Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Print Date: 05/15/2018

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
  - Overalls.
  - ▶ P.V.C.

#### Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

#### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 TOXICOLOGICAL INFORMATION**

# Information on toxicological effects

mormation on toxicological	
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The highly irritant properties of ammonia vapour result as the gas dissolves in mucous fluids and forms irritant, even corrosive solutions. Inhalation of the ammonia fumes causes coughing, vomiting, reddening of lips, mouth, nose, throat and conjunctiva while higher concentrations can cause temporary blindness, restlessness, tightness in the chest, pulmonary oedema (lung damage), weak pulse and cyanosis.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.  Large doses of ammonia or injected ammonium salts may produce diarrhoea and may be sufficiently absorbed to produce increased production of urine and systemic poisoning. Symptoms include weakening of facial muscle, tremor, anxiety, reduced muscle and limb control.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  Mild skin reaction is seen with contact of the vapour of this material on moist skin. High concentrations or direct contact with solutions produces severe pain, a stinging sensation, burns and blisters and possible brown stains.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Prolonged or repeated minor exposure to ammonia gas/vapour may cause long-term irritation to the eyes, nose and upper airway. Repeated exposure or prolonged contact may produce skin inflammation and conjunctivitis.

Chemwatch: 9-528015 Page 6 of 9

Version No: 2.3

# Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Issue Date: 05/03/2018 Print Date: 05/15/2018

Ultra 2010 Exterior Semi Gloss Pastel Base - 40291	TOXICITY	IRRITATION			
	Not Available	Not Available			
	TOXICITY	IRRITATION			
	Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>	Eye (rabbit): 100	mg - mild		
propylene glycol	Oral (rat) LD50: 20000 mg/kg <sup>[2]</sup>	Eye (rabbit): 500	obit): 500 mg/24h - mild		
		Skin(human):104	kin(human):104 mg/3d Intermit Mod		
		Skin(human):500	mg/7days mild		
	TOXICITY	IRRITATION			
titanium dioxide (anatase)	Inhalation (rat) LC50: >2.28 mg/l4 h <sup>[1]</sup>	Not Available			
	Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>	 			
	TOXICITY	IRRITATION			
aluminium hydroxide	Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available			
	TOXICITY	IRRITATION			
residual oils, oxidised	Not Available	Not Available			
Legend:	Value obtained from Europe ECHA Registered Sub- data extracted from RTECS - Register of Toxic Effect of		from manufacturer's SDS. Unless otherwise specified		
TITANIUM DIOXIDE (ANATASE)	exposure to titanium dioxide is via inhalation, swallowing the lungs and immune system.	ng or skin contact. When inhaled, it may de	posit in lung tissue and lymph nodes causing dysfunction		
ALUMINIUM HYDROXIDE & RESIDUAL OILS, OXIDISED	No significant acute toxicological data identified in lite	rature search.			
Acute Toxicity	0	Carcinogenicity	<b>✓</b>		
Skin Irritation/Corrosion	0	Reproductivity	0		
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0		
Respiratory or Skin	0	STOT - Repeated Exposure	0		
sensitisation	9	O.O. Hopoulou Exposulo			

Legend:

A Data available but does not fill the criteria for classification
 Data available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

Ultra 2010 Exterior Semi Gloss Pastel Base - 40291	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	710mg/L	4
propylene glycol	EC50	48	Crustacea	>1000mg/L	4
	EC50	96	Algae or other aquatic plants	19000mg/L	2
	NOEC	168	Fish	98mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	155mg/L	2
Charles Part Information	EC50	48	Crustacea	>10mg/L	2
titanium dioxide (anatase)	EC50	72	Algae or other aquatic plants	5.83mg/L	4
	EC20	72	Algae or other aquatic plants	1.81mg/L	4
	NOEC	336	Fish	0.089mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.2262mg/L	2
aluminium hydroxide	EC50	48	Crustacea	0.7364mg/L	2
	EC50	96	Algae or other aquatic plants	0.0054mg/L	2
	NOEC	72	Algae or other aquatic plants	>=0.004mg/L	2

Chemwatch: **9-528015** Page **7** of **9** 

Version No: 2.3

#### Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Issue Date: **05/03/2018**Print Date: **05/15/2018** 

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
residual oils, oxidised	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	(QSAR) - Aquat	,	IA Registered Substances - Ecotoxicological Informat A, Ecotox database - Aquatic Toxicity Data 5. ECETO Concentration Data 8. Vendor Data		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment

For Diuron: Vapor pressure: 6.90 x10-8 mm Hg (25 C); Henry's law constant: 5.10 x 10-10 atm m3 mol-1.

Atmospheric Fate: Diuron is non-volatile in the atmosphere and is unlikely to be dispersed over large areas.

Atmospheric Fate: Ammonia reacts rapidly with available acids (mainly sulfuric, nitric, and sometimes hydrochloric acid) to form the corresponding salts. Ammonia is persistent in the air.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
titanium dioxide (anatase)	HIGH	HIGH

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
titanium dioxide (anatase)	LOW (BCF = 10)

#### Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
titanium dioxide (anatase)	LOW (KOC = 23.74)

# **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Product / Packaging disposal

- ► Containers may still present a chemical hazard/ danger when empty.
- ► Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- $\blacktriangleright \ \ \text{Recycle wherever possible or consult manufacturer for recycling options}.$
- ▶ Consult State Land Waste Authority for disposal.

# **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

Marine Pollutant NO

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# **SECTION 15 REGULATORY INFORMATION**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

## PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Rhode Island Hazardous Substance List	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US AIHA Workplace Environmental Exposure Levels (WEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances

TITANIUM DIOXIDE (ANATASE)(1317-70-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 9-528015 Page 8 of 9 Issue Date: 05/03/2018
Version No: 2.3 Print Date: 05/15/2018

Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants Monographs US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US - Alaska Limits for Air Contaminants Contaminants  $\ensuremath{\mathsf{US}}$  - Washington Permissible exposure limits of air contaminants US - California Proposition 65 - Carcinogens US - Hawaii Air Contaminant Limits US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) US - Idaho - Limits for Air Contaminants US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) - Carcinogens US - Michigan Exposure Limits for Air Contaminants US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule US - Minnesota Permissible Exposure Limits (PELs) US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-1) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Pennsylvania - Hazardous Substance List US - Rhode Island Hazardous Substance List US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements

#### ALUMINIUM HYDROXIDE(21645-51-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
(CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Hawaii Air Contaminant Limits	US NIOSH Recommended Exposure Limits (RELs)
US - Michigan Exposure Limits for Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Washington Permissible exposure limits of air contaminants	

#### RESIDUAL OILS, OXIDISED(64742-99-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

#### State Regulations

### US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

# US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ

 Chemwatch: 9-528015
 Page 9 of 9
 Issue Date: 05/03/2018

Version No: 2.3

#### Ultra 2010 Exterior Semi Gloss Pastel Base - 40291

Print Date: **05/15/2018** 

Canada - NDSL	N (propylene glycol; residual oils, oxidised; aluminium hydroxide)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (residual oils, oxidised)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	N (residual oils, oxidised)
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

Revision Date	05/03/2018
Initial Date	05/04/2018

#### CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

#### Other information

#### Ingredients with multiple cas numbers

_ <del>-</del>	
Name	CAS No
titanium dioxide (anatase)	1317-70-0, 13463-67-7
aluminium hydroxide	21645-51-2, 1330-44-5, 1302-29-0, 12252-70-9, 51330-22-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

#### **Definitions and abbreviations**

 ${\sf PC-TWA} : {\sf Permissible\ Concentration-Time\ Weighted\ Average}$ 

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.