

ProPaint Interior Paint Flat Bone White - 50818

ICP Construction

Version No: 1.1 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements Issue Date: 05/11/2018 Print Date: 05/15/2018 S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	ProPaint Interior Paint Flat Bone White - 50818
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road MA 01810 United States
Telephone	978-623-9980
Fax	Not Available
Website	https://www.icp-construction.com/
Email	Not Available

Emergency phone number

3, .	
Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Carcinogenicity Category 1A, Specific target organ toxicity - single exposure Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)

Label elements

Hazard pictogram(s)







SIGNAL WORD

DANGER

Hazard statement(s)

H315	Causes skin irritation.
H318	Causes serious eye damage.
H350	May cause cancer.
H370	Causes damage to organs.
H335	May cause respiratory irritation.

Version No: 1.1

Page 2 of 10

ProPaint Interior Paint Flat Bone White - 50818

Issue Date: **05/11/2018** Print Date: **05/15/2018**

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P307+P311	P311 IF exposed: Call a POISON CENTER or doctor/physician.	

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
471-34-1	12.61	calcium carbonate
1317-65-3	9.45	limestone
13463-67-7	5-10	titanium dioxide
7631-86-9	0-0.25	silica amorphous
1332-58-7	<1	kaolin

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Chemwatch: 9-539980 Page 3 of 10 Issue Date: 05/11/2018 Version No: 1.1

ProPaint Interior Paint Flat Bone White - 50818

Print Date: 05/15/2018

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used
- Use extinguishing media suitable for surrounding area

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting

Fire/Explosion Hazard

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear breathing apparatus plus protective gloves in the event of a fire
- Non combustible.

▶ Not considered a significant fire risk, however containers may burn.

May emit poisonous fumes May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills Major Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
	Moderate hazard. ▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs. ► DO NOT allow clothing wet with material to stay in contact with skin
- Other information

Conditions for safe storage, including any incompatibilities

Suitable container

- ► Polyethylene or polypropylene container.
- ▶ Packing as recommended by manufacturer.

▶ is incompatible with acids, ammonium salts, fluorine, germanium, lead diacetate, magnesium, mercurous chloride, silicon, silver nitrate, titanium. Contact with acid generates carbon dioxide gas, which may pressurise and then rupture closed containers

Titanium dioxide

- ▶ reacts with strong acids, strong oxidisers
- reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence
- ▶ dust or powders can ignite and then explode in a carbon dioxide atmosphere

Storage incompatibility

Acetic acid: ▶ vapours forms explosive mixtures with air (above 39 C.)

- reacts violently with bases such as carbonates and hydroxides (giving off large quantities of heat), oxidisers, organic amines, acetaldehyde, potassium
- reacts (sometimes violently), with strong acids, aliphatic amines, alkanolamines, alkylene oxides, epichlorohydrin, acetic anhydride, 2-aminoethanol, ammonia, ammonium nitrate, bromine pentafluoride, chlorosulfonic acid, chromic acid, chromium trioxide, ethylenediamine, ethyleneimine, hydrogen peroxide, isocyanates, oleum, perchloric acid, permanganates, phosphorus isocyanate, phosphorus trichloride, sodium peroxide, xylene
- attacks cast iron, stainless steel and other metals, forming flammable hydrogen gas
- attacks many forms of rubber, plastics and coatings

None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate, Natural calcium carbonate [Note: Marble is a metamorphic form of calcium carbonate.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate, Natural calcium carbonate [Note: Calcite & aragonite are commercially important natural calcium carbonates.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available

Chemwatch: 9-539980

Page 4 of 10

Version No: 1.1 ProPaint Interior Paint Flat Bone White - 50818

Issue Date: **05/11/2018**Print Date: **05/15/2018**

Calcium salt of carbonic acid [Note: Occurs in nature US NIOSH Recommended calcium 10 (total), 5 Not Not as as limestone, chalk, marble, dolomite, aragonite, Not Available Exposure Limits (RELs) carbonate (resp) mg/m3 Available Available calcite and oyster shells.] US OSHA Permissible Exposure calcium Not Not Marble: Total dust 15 mg/m3 Not Available Levels (PELs) - Table Z1 carbonate Available Available US OSHA Permissible Exposure calcium Not Not Calcium carbonate: Total dust 15 mg/m3 Not Available Levels (PELs) - Table Z1 carbonate Available Available US OSHA Permissible Exposure calcium Not Not Marble: Respirable fraction 5 mg/m3 Not Available Levels (PELs) - Table Z1 carbonate Available Available US OSHA Permissible Exposure calcium Not Respirable fraction 5 mg/m3 Not Available Available Levels (PELs) - Table Z1 carbonate Available US OSHA Permissible Exposure calcium Not Not Limestone: Total dust 15 mg/m3 Not Available Levels (PELs) - Table Z1 carbonate Available Available US OSHA Permissible Exposure calcium Not Not Not Available Limestone: Respirable fraction 5 mg/m3 Levels (PELs) - Table Z1 Available carbonate Available Calcium salt of carbonic acid [Note: Occurs in nature US NIOSH Recommended 10 (total), 5 Not Not Not Available limestone as as limestone, chalk, marble, dolomite, aragonite, Exposure Limits (RELs) (resp) mg/m3 Available Available calcite and ovster shells.1 Calcium carbonate, Natural calcium carbonate [Note: US NIOSH Recommended 10 (total), 5 Not Not Available limestone Exposure Limits (RELs) Marble is a metamorphic form of calcium carbonate.] (resp) mg/m3 Available Available Calcium carbonate. Natural calcium carbonate [Note: 10 (total), 5 US NIOSH Recommended Not Not limestone Not Available Calcite & aragonite are commercially important Exposure Limits (RELs) Available Available (resp) mg/m3 natural calcium carbonates.] US OSHA Permissible Exposure Not Not Marble: Respirable fraction Not Available limestone 5 mg/m3 Available Levels (PELs) - Table Z1 Available US OSHA Permissible Exposure Not Not limestone Limestone: Total dust 15 mg/m3 Not Available Available Available Levels (PELs) - Table Z1 US OSHA Permissible Exposure Not Not limestone Marble: Total dust 15 mg/m3 Not Available Available Available Levels (PELs) - Table Z1 US OSHA Permissible Exposure Not Not limestone Limestone: Respirable fraction 5 mg/m3 Not Available Levels (PELs) - Table Z1 Available Available US OSHA Permissible Exposure Not Not limestone Not Available Respirable fraction 5 mg/m3 Available Levels (PELs) - Table Z1 Available US OSHA Permissible Exposure Not Not limestone Calcium carbonate: Total dust 15 mg/m3 Not Available Levels (PELs) - Table Z1 Available Available US NIOSH Recommended titanium Not Not Rutile, Titanium oxide, Titanium peroxide Not Available Ca See Appendix A Exposure Limits (RELs) Available Available dioxide US ACGIH Threshold Limit Values titanium Not Not Titanium dioxide 10 mg/m3 TLV® Basis: LRT irr Available (TLV) dioxide Available US OSHA Permissible Exposure titanium Not Not Titanium dioxide: Total dust 15 mg/m3 Not Available Levels (PELs) - Table Z1 dioxide Available Available Diatomaceous earth, Diatomaceous silica, Diatomite, US NIOSH Recommended silica Not Not Precipitated amorphous silica, Silica gel, Silicon 6 mg/m3 Not Available Exposure Limits (RELs) amorphous Available Available dioxide (amorphous) 80 / (%SiO2) US OSHA Permissible Exposure silica (Name (including natural Not Not Amorphous mg/m3 / 20 Levels (PELs) - Table Z3 amorphous Available Available diatomaceous earth)) mppcf US OSHA Permissible Exposure silica Silica, amorphous, diatomaceous earth, containing Not Not Not Available See Table 7-3 Levels (PELs) - Table Z1 amorphous less than 1% crystalline silica Available Available US OSHA Permissible Exposure silica Not Not Silica, amorphous, precipitated and gel Not Available See Table Z-3 Levels (PELs) - Table Z1 amorphous Available Available US OSHA Permissible Exposure silica Not Not Silica, fused, respirable dust Not Available See Table 7-3 Available Levels (PELs) - Table Z1 amorphous Available China clay, Clay, Hydrated aluminum silicate, Hydrite, US NIOSH Recommended 10 (total), 5 Not Not kaolin Porcelain clay [Note: Main constituent of Kaolin is Not Available Exposure Limits (RELs) Available Available (resp) mg/m3 Kaolinite (Al2Si2O5(OH)4).] US ACGIH Threshold Limit Values Not Not TLV® Basis: kaolin Kaolin 2 mg/m3 (TLV) Available Available Pneumoconiosis

Levels (PELs) - Table Z1 EMERGENCY LIMITS

Levels (PELs) - Table Z1

US OSHA Permissible Exposure

US OSHA Permissible Exposure

kaolin

kaolin

Kaolin: Total dust

Kaolin: Respirable fraction

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
calcium carbonate	Limestone; (Calcium carbonate; Dolomite)	45 mg/m3	500 mg/m3	3,000 mg/m3
calcium carbonate	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1,300 mg/m3
limestone	Limestone; (Calcium carbonate; Dolomite)	45 mg/m3	500 mg/m3	3,000 mg/m3

Not

Not

Available

Available

15 mg/m3

5 mg/m3

Not

Not

Available

Available

Not Available

Not Available

Chemwatch: **9-539980** Page **5** of **10**

Version No: 1.1

ProPaint Interior Paint Flat Bone White - 50818

Issue Date: **05/11/2018**Print Date: **05/15/2018**

limestone	Carbonic acid, calcium salt		45 mg/m3	210 mg/m3	1,300 mg/m3
titanium dioxide	Titanium oxide; (Titanium dioxide)		30 mg/m3	330 mg/m3	2,000 mg/m3
silica amorphous	Silica gel, amorphous synthetic		18 mg/m3	200 mg/m3	1,200 mg/m3
silica amorphous	Silica, amorphous fumed		18 mg/m3	100 mg/m3	630 mg/m3
silica amorphous	Siloxanes and silicones, dimethyl, reaction products with silica; (Hydrophobic silicon dioxide, amorphous)		120 mg/m3	1,300 mg/m3	7,900 mg/m3
silica amorphous	Silica, amorphous furne		45 mg/m3	500 mg/m3	3,000 mg/m3
silica amorphous	Silica amorphous hydrated		18 mg/m3	220 mg/m3	1,300 mg/m3
Ingredient	Original IDLH	Revised IDLH			
calcium carbonate	Not Available	Not Available			
limestone	Not Available	Not Available			
titanium dioxide	5000 mg/m3	Not Available			

Exposure controls

silica amorphous

kaolin

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Not Available

Not Available

Personal protection



3000 mg/m3

Not Available



▶ Wear chemical protective gloves, e.g. PVC.





Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.

Skin protection

See Hand protection below

Hands/feet protection

▶ Wear safety footwear or safety gumboots, e.g. Rubber
The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

Body protection

checked prior to the application.

See Other protection below

Other protection

Overalls.P.V.C.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Issue Date: 05/11/2018 Print Date: 05/15/2018

ProPaint Interior Paint Flat Bone White - 50818

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological eff

Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.		
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	If applied to the eyes, this material causes severe eye damage.		
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.		
DroBoint Interior Boint Flat	TOXICITY	IRRITATION	
ProPaint Interior Paint Flat Bone White - 50818	Not Available	Not Available	
	TOXICITY	IRRITATION	
calcium carbonate	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE	
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate	
	TOXICITY	IRRITATION	
limestone	Oral (rat) LD50: 6450 mg/kg ^[2]	Skin (rabbit): 500 mg/24h-moderate	
	TOXICITY	IRRITATION	
titanium dioxide	Inhalation (rat) LC50: >2.28 mg/l4 h ^[1]	Skin (human): 0.3 mg /3D (int)-mild *	
	Oral (rat) LD50: >2000 mg/kg ^[1]		
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: >5000 mg/kg ^[2]	Eye (rabbit): non-irritating *	
silica amorphous	Inhalation (rat) LC50: >0.139 mg/l/14h**[Grace] ^[2]	Skin (rabbit): non-irritating *	
	Oral (rat) LD50: 3160 mg/kg ^[2]		
	TOXICITY	IRRITATION	
kaolin	Not Available	Not Available	
Legend:	1 Value obtained from Furnne FCHA Registered Substances	Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified	
Legena:	data extracted from RTECS - Register of Toxic Effect of chemica		

TITANIUM DIOXIDE

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

* IUCLID

SILICA AMORPHOUS

For silica amorphous:

of the lungs and immune system.

When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body.

The substance is classified by IARC as Group 3:

Chemwatch: 9-539980 Version No: 1.1

0

Page **7** of **10 ProPaint Interior Paint Flat Bone White - 50818**

Issue Date: 05/11/2018 Print Date: 05/15/2018

	NOT classifiable as to its carcinogenicity to numans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Reports indicate high/prolonged exposures to amorphous silicas induced lung fibrosis in experimental animals; in some experiments these effects were reversible. [PATTYS]		
Acute Toxicity	0	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin	6	0T0T D	8

Legend:

Aspiration Hazard

STOT - Repeated Exposure

X − Data available but does not fill the criteria for classification
 ✓ − Data available to make classification

0

0

○ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

sensitisation

Mutagenicity

Toxicity

DraBaint Interior Daint Flat	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
ProPaint Interior Paint Flat Bone White - 50818	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	>56000mg/L	4
calcium carbonate	EC50	72	Algae or other aquatic plants	>14mg/L	2
	NOEC	72	Algae or other aquatic plants	14mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
P	LC50	96	Fish	>56000mg/L	4
limestone	EC50	72	Algae or other aquatic plants	>14mg/L	2
	NOEC	72	Algae or other aquatic plants	14mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	155mg/L	2
	EC50	48	Crustacea	>10mg/L	2
titanium dioxide	EC50	72	Algae or other aquatic plants	5.83mg/L	4
	EC20	72	Algae or other aquatic plants	1.81mg/L	4
	NOEC	336	Fish	0.089mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	ca.2000mg/L	1
-::	EC50	48	Crustacea	ca.7600mg/L	1
silica amorphous	EC50	72	Algae or other aquatic plants	440mg/L	1
	EC10	72	Algae or other aquatic plants	140mg/L	1
	NOEC	72	Algae or other aquatic plants	60mg/L	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
kaolin	Not Available	Not Available	Not Available	Not Available	Not Available

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH
silica amorphous	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)
silica amorphous	LOW (LogKOW = 0.5294)

Page 8 of 10

ProPaint Interior Paint Flat Bone White - 50818

Issue Date: 05/11/2018 Print Date: 05/15/2018

Mobility in soil

Ingredient	Mobility
titanium dioxide	LOW (KOC = 23.74)
silica amorphous	LOW (KOC = 23.74)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

CALCIUM CARBONATE(471-34-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Massachusetts - Right To Know Listed Chemicals	Contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
	US TSCA Chemical Substance Inventory - Interim List of Active Substances

LIMESTONE(1317-65-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Massachusetts - Right To Know Listed Chemicals	Contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
	US TSCA Chemical Substance Inventory - Interim List of Active Substances

TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California Proposition 65 - Carcinogens	US - Washington Permissible exposure limits of air contaminants
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive)
US - Minnesota Permissible Exposure Limits (PELs)	Rule
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
	US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification
	Requirements

Version No: 1.1

ProPaint Interior Paint Flat Bone White - 50818

Print Date: 05/15/2018

SILICA AMORPHOUS(7631-86-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

 · · · · · ·	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Tennessee Occupational Exposure Limits -
Monographs	US - Vermont Permissible Exposure Limits Table
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of
US - Idaho - Limits for Air Contaminants	US - Washington Toxic air pollutants and their AS
US - Idaho - Toxic and Hazardous Substances - Mineral Dust	US - Wyoming Toxic and Hazardous Substances
US - Massachusetts - Right To Know Listed Chemicals	US - Wyoming Toxic and Hazardous Substances
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RE
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs)
US - Oregon Permissible Exposure Limits (Z-3)	US Toxic Substances Control Act (TSCA) - Cher
US - Pennsylvania - Hazardous Substance List	US TSCA Chemical Substance Inventory - Interir
US - Rhode Island Hazardous Substance List	

- Limits For Air Contaminants
- ole Z-1-A Final Rule Limits for Air Contaminants
- ole Z-1-A Transitional Limits for Air
- of air contaminants
- ASIL, SQER and de minimis emission values
- es Table Z1 Limits for Air Contaminants
- es Table Z-3 Mineral Dusts
- RELs)
- s) Table Z1
- s) Table Z3
- emical Substance Inventory
- erim List of Active Substances

KAOLIN(1332-58-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

RAULIN(1332-36-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS		
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air	
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants	
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants	
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)	
US - Oregon Permissible Exposure Limits (Z-1)	US ACGIH Threshold Limit Values (TLV) - Carcinogens	
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)	
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances	

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ

Chemwatch: 9-539980 Page 10 of 10 Issue Date: 05/11/2018 Version No: 1.1 Print Date: 05/15/2018

ProPaint Interior Paint Flat Bone White - 50818

Canada - NDSL	N (kaolin)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (kaolin)
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	05/11/2018
Initial Date	05/12/2018

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

Name	CAS No
calcium carbonate	471-34-1, 13397-26-7, 15634-14-7, 1317-65-3, 72608-12-9, 878759-26-3, 63660-97-9, 459411-10-0, 198352-33-9, 146358-95-4
titanium dioxide	13463-67-7, 1317-70-0, 1317-80-2, 12188-41-9, 1309-63-3, 100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12701-76-7, 12767-65-6, 12789-63-8, 1344-29-2, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9
silica amorphous	7631-86-9, 112945-52-5, 67762-90-7, 68611-44-9, 68909-20-6, 112926-00-8, 61790-53-2, 60676-86-0, 91053-39-3, 69012-64-2, 844491-94-7
kaolin	1332-58-7, 71888-52-3, 1026990-70-4, 12198-85-5, 12199-11-0, 190086-05-6, 290817-34-4, 384842-32-4, 39406-22-9, 52624-41-6, 849104-81-0, 903527-69-5, 90803-81-9, 944250-63-9, 95077-05-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.