

ProPaint Interior Paint Semi Gloss Bone White - 51018

ICP Construction

Version No: **2.2**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **05/02/2018** Print Date: **05/15/2018** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

| Product name | ProPaint Interior Paint Semi Gloss Bone White - 51018 |
|-------------------------------|-------------------------------------------------------|
| Synonyms | Not Available |
| Other means of identification | Not Available |

Recommended use of the chemical and restrictions on use

Relevant identified uses Interior Pain

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

| Registered company name | ICP Construction |
|-------------------------|-----------------------------------------|
| Address | 150 Dascomb Road MA 01810 United States |
| Telephone | 978-623-9980 |
| Fax | Not Available |
| Website | https://www.icp-construction.com/ |
| Email | Not Available |

Emergency phone number

| • , . | |
|-----------------------------------|----------------|
| Association / Organisation | Chemtel |
| Emergency telephone numbers | 1-800-255-3924 |
| Other emergency telephone numbers | 1-813-248-0585 |

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Eye Irritation Category 2A, Carcinogenicity Category 1A

Label elements

Hazard pictogram(s)





SIGNAL WORD

DANGER

Hazard statement(s)

| ` ' | |
|------|--------------------------------|
| H319 | Causes serious eye irritation. |
| H350 | May cause cancer. |

Hazard(s) not otherwise specified

Not Applicable

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018** Print Date: **05/15/2018**

| P101 | If medical advice is needed, have product container or label at hand. |
|------|-----------------------------------------------------------------------|
| P102 | Keep out of reach of children. |

Precautionary statement(s) Prevention

| P201 | Obtain special instructions before use. |
|------|------------------------------------------------|
| P281 | Use personal protective equipment as required. |

Precautionary statement(s) Response

| P308+P313 | IF exposed or concerned: Get medical advice/attention. | |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |

Precautionary statement(s) Storage

| Precautionary statement(s) Storage | |
|-------------------------------------|------------------|
| P405 | Store locked up. |
| Precautionary statement(s) Disposal | |

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|------------|-----------|------------------|
| 13463-67-7 | 10-20 | titanium dioxide |
| 57-55-6 | 1-5 | propylene glycol |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Dispose of contents/container in accordance with local regulations.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. |
| Ingestion | Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. | |
|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Special protective equipment and precautions for fire-fighters | | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. | |
| Fire/Explosion Hazard | Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous furnes. May emit corrosive furnes. | |

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018**Print Date: **05/15/2018**

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. |
|--------------|------------------------------------------------------------------------------------------|
| Major Spills | Moderate hazard. ▶ Clear area of personnel and move upwind. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ► Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ▶ DO NOT allow clothing wet with material to stay in contact with skin

Other information

Conditions for safe storage, including any incompatibilities

| Suitable container | Polyethylene or polypropylene container. Packing as recommended by manufacturer. | | | |
|--------------------|---------------------------------------------------------------------------------------------------------------|--|--|--|
| | Titanium dioxide ▶ reacts with strong acids, strong oxidisers | | | |

- reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures these reactions involves reduction of the oxide and are accompanied by incandescence
- ▶ dust or powders can ignite and then explode in a carbon dioxide atmosphere

Acetic acid:

Storage incompatibility

- ▶ vapours forms explosive mixtures with air (above 39 C.)
- reacts violently with bases such as carbonates and hydroxides (giving off large quantities of heat), oxidisers, organic amines, acetaldehyde, potassium tert-butoxide
- reacts (sometimes violently), with strong acids, aliphatic amines, alkanolamines, alkylene oxides, epichlorohydrin, acetic anhydride, 2-aminoethanol, ammonia, ammonium nitrate, bromine pentafluoride, chlorosulfonic acid, chromic acid, chromium trioxide, ethylenediamine, ethyleneimine, hydrogen peroxide, isocyanates, oleum, perchloric acid, permanganates, phosphorus isocyanate, phosphorus trichloride, sodium peroxide, xylene
- ▶ attacks cast iron, stainless steel and other metals, forming flammable hydrogen gas
- ▶ attacks many forms of rubber, plastics and coatings

None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|----------------------------------------------------------|------------------|-------------------------------------------|---------------|---------------|---------------|---------------------|
| US NIOSH Recommended Exposure Limits (RELs) | titanium dioxide | Rutile, Titanium oxide, Titanium peroxide | Not Available | Not Available | Not Available | Ca See Appendix A |
| US ACGIH Threshold Limit Values (TLV) | titanium dioxide | Titanium dioxide | 10 mg/m3 | Not Available | Not Available | TLV® Basis: LRT irr |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | titanium dioxide | Titanium dioxide: Total dust | 15 mg/m3 | Not Available | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|------------------|-------------------------------------|----------|-------------|-------------|
| titanium dioxide | Titanium oxide; (Titanium dioxide) | 30 mg/m3 | 330 mg/m3 | 2,000 mg/m3 |
| propylene glycol | Propylene glycol; (1,2-Propanediol) | 30 mg/m3 | 1,300 mg/m3 | 7,900 mg/m3 |

| Ingredient | Original IDLH | Revised IDLH |
|------------------|---------------|---------------|
| titanium dioxide | 5000 mg/m3 | Not Available |
| propylene glycol | Not Available | Not Available |


Exposure controls

| Appropriate engineering | |
|-------------------------|--|
| controls | |

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018**Print Date: **05/15/2018**



SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Appearance | Not Available | | |
|----------------------------------------------|---------------|-----------------------------------------|---------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water (g/L) | Immiscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| Reactivity | See section 7 |
|------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

| Inhaled | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ingestion | The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. |
| Skin Contact | Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye | This material can cause eye irritation and damage in some persons. |

Chemwatch: **9-535983** Page **5** of **8**

Version No: 2.2

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018**Print Date: **05/15/2018**

Chronic

Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

| TOXICITY | IRRITATION | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Not Available | Not Available | |
| TOXICITY | IRRITATION | |
| Inhalation (rat) LC50: >2.28 mg/l4 h ^[1] | Skin (human): 0.3 mg /3D (int)-mild * | |
| Oral (rat) LD50: >2000 mg/kg ^[1] | | |
| TOXICITY | IRRITATION | |
| Dermal (rabbit) LD50: 11890 mg/kg ^[2] | Eye (rabbit): 100 mg - mild | |
| Oral (rat) LD50: 20000 mg/kg ^[2] | Eye (rabbit): 500 mg/24h - mild | |
| | Skin(human):104 mg/3d Intermit Mod | |
| | Skin(human):500 mg/7days mild | |
| Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | |
| | Not Available TOXICITY Inhalation (rat) LC50: >2.28 mg/l4 h ^[1] Oral (rat) LD50: >2000 mg/kg ^[1] TOXICITY Dermal (rabbit) LD50: 11890 mg/kg ^[2] Oral (rat) LD50: 20000 mg/kg ^[2] | |

TITANIUM DIOXIDE

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

* IUCLID

| Acute Toxicity | 0 | Carcinogenicity | ✓ |
|-----------------------------------|---|--------------------------|---|
| Skin Irritation/Corrosion | 0 | Reproductivity | 0 |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | 0 |
| Respiratory or Skin sensitisation | 0 | STOT - Repeated Exposure | 0 |
| Mutagenicity | 0 | Aspiration Hazard | 0 |

Legend:

X − Data available but does not fill the criteria for classification

✓ – Data available to make classification
 ○ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| ProPaint Interior Paint Semi Gloss Bone White - 51018 | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|----------------------------------------------------------|------------------|--------------------|-------------------------------|------------------|------------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
| | LC50 | 96 | Fish | 155mg/L | 2 |
| | EC50 | 48 | Crustacea | >10mg/L | 2 |
| titanium dioxide | EC50 | 72 | Algae or other aquatic plants | 5.83mg/L | 4 |
| | EC20 | 72 | Algae or other aquatic plants | 1.81mg/L | 4 |
| | NOEC | 336 | Fish | 0.089mg/L | 4 |
| | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
| | LC50 | 96 | Fish | 710mg/L | 4 |
| propylene glycol | EC50 | 48 | Crustacea | >1000mg/L | 4 |
| | EC50 | 96 | Algae or other aquatic plants | 19000mg/L | 2 |
| | NOEC | 168 | Fish | 98mg/L | 4 |

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient Persistence: Water/Soil Persistence: Air

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018**Print Date: **05/15/2018**

| titanium dioxide | HIGH | HIGH |
|------------------|------|------|
| propylene glycol | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------------|-----------------|
| titanium dioxide | LOW (BCF = 10) |
| propylene glycol | LOW (BCF = 1) |

Mobility in soil

| Ingredient | Mobility |
|------------------|-------------------|
| titanium dioxide | LOW (KOC = 23.74) |
| propylene glycol | HIGH (KOC = 1) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- ► Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants Monographs US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US - Alaska Limits for Air Contaminants Contaminants US - California Proposition 65 - Carcinogens US - Washington Permissible exposure limits of air contaminants US - Hawaii Air Contaminant Limits US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) - Carcinogens US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) US - Michigan Exposure Limits for Air Contaminants US - Minnesota Permissible Exposure Limits (PELs) Rule US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-1) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Pennsylvania - Hazardous Substance List US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - Rhode Island Hazardous Substance List US TSCA Chemical Substance Inventory - Interim List of Active Substances US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements

PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| US - Pennsylvania - Hazardous Substance List | US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs) |
|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| US - Rhode Island Hazardous Substance List | US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants |
| US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
| US AIHA Workplace Environmental Exposure Levels (WEELs) | US TSCA Chemical Substance Inventory - Interim List of Active Substances |

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

| Flammable (Gases, Aerosols, Liquids, or Solids) | | No |
|-------------------------------------------------|--------------------|----|
| | Gas under pressure | No |

ProPaint Interior Paint Semi Gloss Bone White - 51018

Issue Date: **05/02/2018**Print Date: **05/15/2018**

| Explosive | No |
|--------------------------------------------------------------|-----|
| · | |
| Self-heating | No |
| Pyrophoric (Liquid or Solid) | No |
| Pyrophoric Gas | No |
| Corrosive to metal | No |
| Oxidizer (Liquid, Solid or Gas) | No |
| Organic Peroxide | No |
| Self-reactive | No |
| In contact with water emits flammable gas | No |
| Combustible Dust | No |
| Carcinogenicity | Yes |
| Acute toxicity (any route of exposure) | No |
| Reproductive toxicity | No |
| Skin Corrosion or Irritation | No |
| Respiratory or Skin Sensitization | No |
| Serious eye damage or eye irritation | Yes |
| Specific target organ toxicity (single or repeated exposure) | No |
| Aspiration Hazard | No |
| Germ cell mutagenicity | No |
| Simple Asphyxiant | No |
| | |

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

| National Inventory | Status |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Australia - AICS | Y |
| Canada - DSL | Υ |
| Canada - NDSL | N (propylene glycol) |
| China - IECSC | Y |
| Europe - EINEC / ELINCS / NLP | Y |
| Japan - ENCS | Y |
| Korea - KECI | Υ |
| New Zealand - NZIoC | Y |
| Philippines - PICCS | Υ |
| USA - TSCA | Y |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION

| Revision Date | 05/02/2018 |
|---------------|------------|
| Initial Date | 05/03/2018 |

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| titanium dioxide | 13463-67-7, 1317-70-0, 1317-80-2, 12188-41-9, 1309-63-3, 100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12701-76-7, 12767-65-6, 12789-63-8, 1344-29-2, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

 Chemwatch: 9-535983
 Page 8 of 8
 Issue Date: 05/02/2018

Version No: 2.2

ProPaint Interior Paint Semi Gloss Bone White - 51018

Print Date: 05/15/2018

Definitions and abbreviations

 $\begin{array}{ll} {\sf PC-TWA: Permissible Concentration-Time Weighted \ Average} \\ {\sf PC-STEL: Permissible Concentration-Short Term \ Exposure \ Limit} \end{array}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.