



CalPro Interior Paint Eggshell China White - 55714

ICP Construction

Version No: 2.2
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **10/11/2018**
Print Date: **10/11/2018**
S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	CalPro Interior Paint Eggshell China White - 55714
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Interior Paint
--------------------------	----------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road Andover MA United States
Telephone	978-623-9980
Fax	Not Available
Website	http://www.icp-construction.com/
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1
----------------	---

Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	DANGER
-------------	---------------

Hazard statement(s)

H315	Causes skin irritation.
H318	Causes serious eye damage.

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
------	--

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
57-55-6	1-5	<u>propylene glycol</u>
1317-65-3	10-15	<u>limestone</u>
13463-67-7	10-20	<u>titanium dioxide</u>
1314-23-4	0-0.46	<u>zirconium dioxide</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES**Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire.
----------------------	--

Fire/Explosion Hazard

- ▶ Non combustible.
 - ▶ Not considered a significant fire risk, however containers may burn.
- May emit poisonous fumes.
May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Polyethylene or polypropylene container. ▶ Packing as recommended by manufacturer.
Storage incompatibility	<p>Titanium dioxide</p> <ul style="list-style-type: none"> ▶ reacts with strong acids, strong oxidisers ▶ reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence ▶ dust or powders can ignite and then explode in a carbon dioxide atmosphere <p>Acetic acid:</p> <ul style="list-style-type: none"> ▶ vapours forms explosive mixtures with air (above 39 C.) ▶ reacts violently with bases such as carbonates and hydroxides (giving off large quantities of heat), oxidisers, organic amines, acetaldehyde, potassium tert-butoxide ▶ reacts (sometimes violently), with strong acids, aliphatic amines, alkanolamines, alkylene oxides, epichlorohydrin, acetic anhydride, 2-aminoethanol, ammonia, ammonium nitrate, bromine pentafluoride, chlorosulfonic acid, chromic acid, chromium trioxide, ethylenediamine, ethyleneimine, hydrogen peroxide, isocyanates, oleum, perchloric acid, permanganates, phosphorus isocyanate, phosphorus trichloride, sodium peroxide, xylene ▶ attacks cast iron, stainless steel and other metals, forming flammable hydrogen gas ▶ attacks many forms of rubber, plastics and coatings <p>None known</p>

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium salt of carbonic acid [Note: Occurs in nature as as limestone, chalk, marble, dolomite, aragonite, calcite and oyster shells.]	10 (total), 5 (resp) mg/m ³	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium carbonate, Natural calcium carbonate [Note: Calcite & aragonite are commercially important natural calcium carbonates.]	10 (total), 5 (resp) mg/m ³	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium carbonate, Natural calcium carbonate [Note: Marble is a metamorphic form of calcium carbonate.]	10 (total), 5 (resp) mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Marble: Respirable fraction	5 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Limestone: Respirable fraction	5 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Limestone: Total dust	15 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Respirable fraction	5 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Calcium carbonate: Total dust	15 mg/m ³	Not Available	Not Available	Not Available

Continued...

CalPro Interior Paint Eggshell China White - 55714


US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Marble: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide	Rutile, Titanium oxide, Titanium peroxide	Not Available	Not Available	Not Available	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	titanium dioxide	Titanium dioxide: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	zirconium dioxide	Zirconium and compounds, as Zr	5 mg/m3	10 mg/m3	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	zirconium dioxide	Zirconium compounds (as Zr)	5 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Polypropylene glycols	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
limestone	Limestone; (Calcium carbonate; Dolomite)	45 mg/m3	500 mg/m3	3,000 mg/m3
limestone	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1,300 mg/m3
titanium dioxide	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3
zirconium dioxide	Zirconium oxide	14 mg/m3	110 mg/m3	680 mg/m3

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
limestone	Not Available	Not Available
titanium dioxide	5,000 mg/m3	Not Available
zirconium dioxide	25 mg/m3	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C.

Respiratory protection

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	<p>This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

CalPro Interior Paint Eggshell China White - 55714	TOXICITY	IRRITATION
	Not Available	Not Available
propylene glycol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild
	Inhalation (rat) LC50: >44.9 mg/l/4h ^[2]	Eye (rabbit): 500 mg/24h - mild
	Oral (rat) LD50: 20000 mg/kg ^[2]	Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild
limestone	TOXICITY	IRRITATION
	Oral (rat) LD50: 6450 mg/kg ^[2]	Skin (rabbit): 500 mg/24h-moderate
titanium dioxide	TOXICITY	IRRITATION
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Skin (human): 0.3 mg /3D (int)-mild *
	Inhalation (rat) LC50: >2.28 mg/l/4 h ^[1]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
zirconium dioxide	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with
------------------	--

	consuming foods or supplements which contain 1g/kg of PG at most.
LIMESTONE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Eye (rabbit) 0.75: mg/24h - No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects.
TITANIUM DIOXIDE	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. * IUCLID
ZIRCONIUM DIOXIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. No significant acute toxicological data identified in literature search.
PROPYLENE GLYCOL & LIMESTONE & TITANIUM DIOXIDE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	☉	Carcinogenicity	☉
Skin Irritation/Corrosion	✓	Reproductivity	☉
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	☉
Respiratory or Skin sensitisation	☉	STOT - Repeated Exposure	☉
Mutagenicity	☉	Aspiration Hazard	☉

Legend: ✗ - Data available but does not fill the criteria for classification
✓ - Data available to make classification
☉ - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

CalPro Interior Paint Eggshell China White - 55714	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
propylene glycol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	40-613mg/L	2
	EC50	48	Crustacea	43-500mg/L	2
	EC50	96	Algae or other aquatic plants	19-100mg/L	2
	NOEC	168	Fish	11-530mg/L	2
limestone	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>56000mg/L	4
	EC50	72	Algae or other aquatic plants	>14mg/L	2
	NOEC	72	Algae or other aquatic plants	14mg/L	2
titanium dioxide	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	155mg/L	2
	EC50	48	Crustacea	19.3mg/L	2
	EC50	72	Algae or other aquatic plants	5.83mg/L	4
	NOEC	336	Fish	0.089mg/L	4
zirconium dioxide	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72	Algae or other aquatic plants	>0.042mg/L	2
	NOEC	72	Algae or other aquatic plants	0.004mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
titanium dioxide	HIGH	HIGH

Continued...

zirconium dioxide	HIGH	HIGH
-------------------	------	------

Bioaccumulative potential

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
titanium dioxide	LOW (BCF = 10)
zirconium dioxide	LOW (LogKOW = 1.429)

Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
titanium dioxide	LOW (KOC = 23.74)
zirconium dioxide	LOW (KOC = 23.74)

SECTION 13 DISPOSAL CONSIDERATIONS**Waste treatment methods**

Product / Packaging disposal	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
-------------------------------------	--

SECTION 14 TRANSPORT INFORMATION**Labels Required**

Marine Pollutant	NO
-------------------------	----

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture****PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

US - Pennsylvania - Hazardous Substance List	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Rhode Island Hazardous Substance List	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US AIHA Workplace Environmental Exposure Levels (WEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances

LIMESTONE(1317-65-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Washington Permissible exposure limits of air contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Rhode Island Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances

TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Proposition 65 - Carcinogens	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV)
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Massachusetts - Right To Know Listed Chemicals	US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Pennsylvania - Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Rhode Island Hazardous Substance List	US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	

ZIRCONIUM DIOXIDE(1314-23-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Rhode Island Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

National Inventory Status

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y

Canada - NDSL	N (zirconium dioxide; propylene glycol)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	10/11/2018
Initial Date	06/08/2018

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

Name	CAS No
titanium dioxide	13463-67-7, 1317-70-0, 1317-80-2, 12188-41-9, 1309-63-3, 100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12701-76-7, 12767-65-6, 12789-63-8, 1344-29-2, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.