



# Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

## ICP Building Solutions Group

Version No: 2.4

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 10/14/2019

Print Date: 10/14/2019

S.GHS.USA.EN

### SECTION 1 IDENTIFICATION

#### Product Identifier

Product name	Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493
Synonyms	Not Available
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

Relevant identified uses	Interior Paint
--------------------------	----------------

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group
Address	150 Dascomb Road Andover MA United States
Telephone	1-978-623-9980
Fax	Not Available
Website	<a href="http://www.icpgroup.com">http://www.icpgroup.com</a>
Email	Not Available

#### Emergency phone number

Association / Organisation	ChemTel
Emergency telephone numbers	800-424-0300
Other emergency telephone numbers	Not Available

### SECTION 2 HAZARD(S) IDENTIFICATION

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Carcinogenicity Category 1A, Germ cell mutagenicity Category 2
----------------	--

#### Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	DANGER
-------------	--------

#### Hazard statement(s)

H350	May cause cancer.
H341	Suspected of causing genetic defects.

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) General

Continued...

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P281	Use personal protective equipment as required.

**Precautionary statement(s) Response**

P308+P313	IF exposed or concerned: Get medical advice/attention.
-----------	--

**Precautionary statement(s) Storage**

P405	Store locked up.
------	------------------

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container in accordance with local regulations.
------	---

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
124-68-5	<1	<u>monoisobutanolamine</u>
7632-00-0	<1	<u>sodium nitrite</u>
13463-67-7	1-10	<u>titanium dioxide</u>
25265-77-4	<1	<u>2,2,4-trimethyl-1,3-pentanediol monoisobutyrate</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4 FIRST-AID MEASURES****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

**Most important symptoms and effects, both acute and delayed**

See Section 11

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 FIRE-FIGHTING MEASURES****Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Special protective equipment and precautions for fire-fighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> </ul>
----------------------	---

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> </ul> Combustion products include: carbon dioxide (CO <sub>2</sub> ) silicon dioxide (SiO <sub>2</sub> ) metal oxides other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.
------------------------------	---

**SECTION 6 ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> </ul>
<b>Major Spills</b>	Moderate hazard. <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 HANDLING AND STORAGE****Precautions for safe handling**

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	Titanium dioxide <ul style="list-style-type: none"> <li>▶ reacts with strong acids, strong oxidisers</li> <li>▶ reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence</li> <li>▶ dust or powders can ignite and then explode in a carbon dioxide atmosphere</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide	Rutile, Titanium oxide, Titanium peroxide	Not Available	Not Available	Not Available	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	titanium dioxide	Titanium dioxide	10 mg/m <sup>3</sup>	Not Available	Not Available	TLV® Basis: LRT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	titanium dioxide	Titanium dioxide: Total dust	15 mg/m <sup>3</sup>	Not Available	Not Available	Not Available

**EMERGENCY LIMITS**


Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
monoisobutanolamine	Isobutanol-2-amine	17 mg/m <sup>3</sup>	190 mg/m <sup>3</sup>	570 mg/m <sup>3</sup>
sodium nitrite	Sodium nitrite	6.4 mg/m <sup>3</sup>	71 mg/m <sup>3</sup>	240 mg/m <sup>3</sup>
titanium dioxide	Titanium oxide; (Titanium dioxide)	30 mg/m <sup>3</sup>	330 mg/m <sup>3</sup>	2,000 mg/m <sup>3</sup>
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Trimethyl-1,3-pentanediol monoisobutyrate, 2,2,4-; (Texanol)	13 mg/m <sup>3</sup>	140 mg/m <sup>3</sup>	840 mg/m <sup>3</sup>
Ingredient	Original IDLH	Revised IDLH		

Continued...

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

monoisobutanolamine	Not Available	Not Available
sodium nitrite	Not Available	Not Available
titanium dioxide	5,000 mg/m <sup>3</sup>	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available

## Exposure controls

<b>Appropriate engineering controls</b>	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C.</li> </ul>

## Respiratory protection

Type A Filter of sufficient capacity (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

<b>Appearance</b>	Not Available		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Available
<b>Flash point (°C)</b>	Not Available	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Available	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> </ul>

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The odour of isopropanol may give some warning of exposure, but odour fatigue may occur. Inhalation of isopropanol may produce irritation of the nose and throat with sneezing, sore throat and runny nose.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Swallowing 10 millilitres of isopropanol may cause serious injury; 100 millilitres may be fatal if not properly treated. The adult single lethal dose is approximately 250 millilitres.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. 511ipa
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Isopropanol vapour may cause mild eye irritation at 400 parts per million. Splashes may cause severe eye irritation, possible burns to the cornea and eye damage.
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Prolonged inhalation of high concentrations of magnesite (magnesium carbonate) dust caused pulmonary deposition and retention. Roasted magnesite (magnesium oxide) produced a greater degree of fibrosis than did crude magnesite. Long term, or repeated exposure of isopropanol may cause inco-ordination and tiredness. Repeated inhalation exposure to isopropanol may produce sleepiness, inco-ordination and liver degeneration. Overexposure to the breathable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity and chest infections.

Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
monoisobutanolamine	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup> Oral (rat) LD50: 2900 mg/kg <sup>[2]</sup>	Not Available
sodium nitrite	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation (rat) LC50: 0.0055 mg/l/4h <sup>[2]</sup> Oral (rat) LD50: =85 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg/24hr - mild
titanium dioxide	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup> Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Skin (human): 0.3 mg /3D (int)-mild * Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >15200 mg/kg <sup>[2]</sup> Inhalation (rat) LC50: >5.325 mg/l/6h <sup>[2]</sup> Oral (rat) LD50: 3200 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Eyes - Moderate irritant * Skin - Slight irritant * Skin (rabbit): mild *** Skin: no adverse effect observed (not irritating) <sup>[1]</sup>

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

<b>MONOISOBUTANOLAMINE</b>	TRIS AMINO and its surrogate chemicals have very little, if any, toxicity. They are mildly irritating to eyes at moderate concentrations, and do not cause allergic skin reactions.
<b>SODIUM NITRITE</b>	Tumorigenic - Carcinogenic by RTECS criteria.
<b>TITANIUM DIOXIDE</b>	* IUCLID Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. No significant acute toxicological data identified in literature search. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  <b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
<b>2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE</b>	Not a skin sensitizer (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** [SWIFT] ** [Eastman] *** [Perstop]
<b>Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493 &amp; SODIUM NITRITE &amp; TITANIUM DIOXIDE</b>	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.
<b>SODIUM NITRITE &amp; 2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE</b>	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
<b>TITANIUM DIOXIDE &amp; 2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✓
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✗
<b>Serious Eye Damage/Irritation</b>	✗	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✓	<b>Aspiration Hazard</b>	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

monoisobutanolamine	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	=100mg/L	1
	EC50	48	Crustacea	=193mg/L	1
	EC50	96	Algae or other aquatic plants	52.872mg/L	3
	NOEC	48	Crustacea	100mg/L	2

sodium nitrite	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.048mg/L	4
	EC50	48	Crustacea	ca.12.5100mg/L	1
	EC50	96	Algae or other aquatic plants	12.537mg/L	3
NOEC	96	Fish	0.02mg/L	4	

titanium dioxide	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
	EC50	48	Crustacea	>1-mg/L	2
	EC50	72	Algae or other aquatic plants	5.83mg/L	4
NOEC	336	Fish	0.089mg/L	4	

2,2,4-trimethyl-1,3-pentenediol monoisobutyrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	9.552mg/L	3
	EC50	48	Crustacea	>19mg/L	2
	EC50	96	Algae or other aquatic plants	0.789mg/L	3
NOEC	72	Algae or other aquatic plants	2mg/L	2	

Continued...

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Surfactants: Kow cannot be easily determined due to hydrophilic/hydrophobic properties of the molecules in surfactants. BCF value: 1-350.

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
monoisobutanolamine	LOW	LOW
sodium nitrite	LOW	LOW
titanium dioxide	HIGH	HIGH
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW	LOW

**Bioaccumulative potential**

Ingredient	Bioaccumulation
monoisobutanolamine	LOW (BCF = 330)
sodium nitrite	LOW (LogKOW = 0.0564)
titanium dioxide	LOW (BCF = 10)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)

**Mobility in soil**

Ingredient	Mobility
monoisobutanolamine	MEDIUM (KOC = 2.196)
sodium nitrite	LOW (KOC = 23.74)
titanium dioxide	LOW (KOC = 23.74)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Product / Packaging disposal</b>	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> </ul>
-------------------------------------	--

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

<b>Marine Pollutant</b>	NO
-------------------------	----

**Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****MONISOBUTANOLAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

GESAMP/EHS Composite List - GESAMP Hazard Profiles	US DOE Temporary Emergency Exposure Limits (TEELs)
IMO IBC Code Chapter 17: Summary of minimum requirements	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US Coast Guard, Department of Homeland Security Part 153: Ships Carrying Bulk Liquid, Liquefied gas or compressed gas hazardous materials. Table 1 to Part 153 --Summary of Minimum Requirements	

**SODIUM NITRITE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

GESAMP/EHS Composite List - GESAMP Hazard Profiles	US Department of Transportation (DOT), Hazardous Material Table
IMO IBC Code Chapter 17: Summary of minimum requirements	US DOE Temporary Emergency Exposure Limits (TEELs)
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	US EPCRA Section 313 Chemical List
International Air Transport Association (IATA) Dangerous Goods Regulations	US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide
International Maritime Dangerous Goods Requirements (IMDG Code)	US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID) Number
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Coast Guard, Department of Homeland Security Part 153: Ships Carrying Bulk Liquid, Liquefied gas or compressed gas hazardous materials. Table 1 to Part 153 --Summary of Minimum Requirements	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US CWA (Clean Water Act) - List of Hazardous Substances	US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements
US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides	US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)

**TITANIUM DIOXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

GESAMP/EHS Composite List - GESAMP Hazard Profiles	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
IMO IBC Code Chapter 17: Summary of minimum requirements	US ACGIH Threshold Limit Values (Spanish)
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	US ACGIH Threshold Limit Values (TLV)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US AIHA Workplace Environmental Exposure Levels (WEELs)
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)	US Chemical Footprint Project - Chemicals of High Concern List
US - Alaska Limits for Air Contaminants	US DOE Temporary Emergency Exposure Limits (TEELs)
US - California Proposition 65 - Carcinogens	US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule
US - Hawaii Air Contaminant Limits	US NIOSH Recommended Exposure Limits (RELs)
US - Idaho - Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs) (Spanish)
US - Michigan Exposure Limits for Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)
US - Oregon Permissible Exposure Limits (Z-1)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)
US - Washington Permissible exposure limits of air contaminants	

**2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

GESAMP/EHS Composite List - GESAMP Hazard Profiles	US DOE Temporary Emergency Exposure Limits (TEELs)
IMO IBC Code Chapter 17: Summary of minimum requirements	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US Coast Guard, Department of Homeland Security Part 153: Ships Carrying Bulk Liquid, Liquefied gas or compressed gas hazardous materials. Table 1 to Part 153 --Summary of Minimum Requirements	

**Federal Regulations****Superfund Amendments and Reauthorization Act of 1986 (SARA)****SECTION 311/312 HAZARD CATEGORIES**

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	Yes
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

**US EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)**

Continued...

## Ultra Aquaborne Ceramic Interior Matte Deep Base - 75493

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Sodium nitrite	100	45.4

## State Regulations

## US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

## US - CALIFORNIA PROPOSITION 65 - CARCINOGENS: LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

## National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (monoisobutanolamine; sodium nitrite; 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

<b>Revision Date</b>	10/14/2019
<b>Initial Date</b>	10/09/2019

## CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

## SDS Version Summary

Version	Issue Date	Sections Updated
1.4.1.1.1	10/14/2019	Ingredients

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

## Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average  
 PC – STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL: No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

Powered by AuthorTe, from Chemwatch.