

WipeOut II Alkyd Stain Blocker - 201 Series

Product Description

This premium quality fast dry white primer- sealer prevents multiple migrating or bleeding stains which show through other primers. It can be used exterior without the fear of water sensitivity of pigmented shellacs. It will seal knots and resin areas on all wood and seal fire damaged surfaces after proper preparation.

Recommended Use

Sheetrock, plaster, wallboard, wood, primed metal, acoustic tiles

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

Application

Notes:

1. On very porous or heavily stained surfaces a second coat of Wipe-Out may be necessary .
2. If used as a spot primer on bare surfaces interior and exterior, a full coat of the proper primer should be applied before the finish coat.

Clean up

Clean tools and equipment with mineral spirits or turpentine. Do not use water on natural bristle or china bristle brushes.

Architectural Specifications

General Surfaces:

- 1 Coat Wipe-Out 20100
- 2 coats California, Latex or Alkyd in desired finish

Notes:

1. On very porous or heavily stained surfaces a second coat of Wipe-Out may be necessary .
2. If used as a spot primer on bare surfaces interior and exterior, a full coat of the proper primer should be applied before the finish coat.

Precautions

Do not mix with water, oils, other paint types. Do not apply when air or surface temperature is below 40° F or when drying conditions are poor. Do not apply when rain, fog or dew is imminent. Do not use on large exterior areas or dimensionally unstable exterior wood such as siding. Spot touch the necessary areas only.

Environmental Health and Safety Information

CAUTION COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

WipeOut II Alkyd Stain Blocker - 201 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

CAUTION! Combustible Liquid: Keep away from heat and flame. Close container after each use. Use only with adequate ventilation. Wash thoroughly after handling. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. KEEP OUT OF REACH OF CHILDREN. Working with flammables and combustibles: Fire extinguishers, a safety shower, and fire blankets must be immediately available. Use only explosion-proof electrical equipment, including lighting. Do not leave any material or equipment unattended.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery, recycling and disposal for regulations.

Place the rags in an empty metal container that has a tight metal lid such as a paint or stain can. Fill the container with water until the rags are submerged; Fill Place the metal lid tightly over the water soaked formerly combustible rags. Place lid tightly on container. Coontact local municipal offices for disposal directions. Never dump solvent down any household or external drains or in any open water.

Technical Data

Product Type	Primer
Exposure	Interior/ Exterior
Specular Gloss	6° ± 2
Volume Solids	55.5% ± 2
Weight Solids	77.0% ± 2
Vehicle Solids	37.3% ± 2
Pigment	62.7% ± 2
Wet Film Thickness	4 mils
Dry Film Thickness	2.3 mils
Viscosity @ 77 °F	78KU ± 5
Max VOC	350 g/l
Flash Point ° F	Combustible
Thinner	Mineral Spirits
Clean - up	Mineral Spirits

Surface Spread Rate

Smooth	400-450 s.f./gal.
Porous	300-350 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	30 minutes
To Handle	4 hours
To Recoat	2 hours
To Wash	

(@ 70 - 77 °F, 50% R.H.)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	China Bristle, Natural Bristle
Roller	3/8" - 1/2" Nap
Airless Spray	

Available Package Sizes

Gallon	Quart
(Weight Per Gallon: 12.6 lbs. ± .5 lb)	

Available Colors and Bases

Available in 0 stock colors

Notes

WipeOut II Alkyd Stain Blocker - 201 Series