

## Sand Finish - 475 Series

### Product Description

This heavy bodied white 100% acrylic latex texture paint can be used to create a unique and distinctive sand plaster finish. It will mask hair line cracks and imperfections and may be painted over with any latex to provide a colored sand finish.

### Recommended Use

Plaster, sheetrock, wallboard, masonry, plywood.

### General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.

Prime knots with WipeOut II Oil-Based stain blocking primer.

### Application

Use a 4" brush (synthetic bristle) or roller. Many unique designs may be formed using a sponge, whisk broom, wad of paper, trowel or kitchen spatula. Apply about one square yard at a time, completing the pattern in one area before going on to the next. After texturing, draw a painter's guide or straight edge across the surface to eliminate sharp points. Sand Finish is self-priming over bare sheet rock, composition board, ceiling tile and concrete.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Plaster, Wallboard, Sheetrock, Concrete, Non-Porous Masonry:

1 coat Prime Choice™ All Surface Acrylic Primer

1 coat Sand Finish 47500

or

2 coats Sand Finish 47500

Porous Masonry and Block:

1 coat Mason-Cote® Block Filler F37500

1 or 2 coats Sand Finish 47500

Wood:

1 coat Prime Choice All Surface Acrylic Primer

1 or 2 coats Sand Finish 47500

Note: If a distinctive or different texture is desired, a small test patch should be done to determine the desired appearance.

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F

## Sand Finish - 475 Series

or when drying conditions are poor. Keep from freezing.

### Environmental Health and Safety Information

**KEEP OUT OF REACH OF CHILDREN. Avoid prolonged contact with skin or breathing of spray mist. Do not take internally. Close container after each use. Use with adequate ventilation.**

Keep from freezing.

## Sand Finish - 475 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

### Technical Data

<b>Product Type</b>	Specialty
<b>Exposure</b>	Interior
<b>Specular Gloss</b>	4° ± 2
<b>Volume Solids</b>	47% ± 2
<b>Weight Solids</b>	67% ± 2
<b>Vehicle Solids</b>	42% ± 2
<b>Pigment</b>	58% ± 2
<b>Wet Film Thickness</b>	17 mils
<b>Dry Film Thickness</b>	8 mils
<b>Viscosity @ 77 °F</b>	80-90KU ± 5
<b>Max VOC</b>	50 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water

### Surface Spread Rate

<b>Smooth</b>	90-110 s.f./gal.
<b>Porous</b>	70-90 s.f./gal.
(Spray Application is 50% of above)	

### Drying Times

<b>To Touch</b>	1 hour
<b>To Handle</b>	4 hours
<b>To Recoat</b>	2 hours
<b>To Wash</b>	14 Day Minimum
(@ 70 - 77 °F, 50% R.H.)	

### Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

### Storage Temperature

Store Between Over 35°F to Under 100°F

### Tools & Equipments

<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" -3/4" Nap Synthetic Fiber
<b>Airless Spray</b>	

### Available Package Sizes

Gallon	
(Weight Per Gallon:13.5 lbs. ± .5 lb)	

### Available Colors and Bases

Available in 0 stock colors