

Preference Interior Paint Eggshell - 507 Series

Product Description

This economical rapid-drying finish is a good choice for new or existing walls and ceilings that are in need of production application or color change.

Recommended Use

Sheetrock, Wallboard, Masonry Block, Primed Metal

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Application

California Preference is ready to use from the can and can be altered slightly for spray application. Please stir well before applying. Keep a wet edge and do not roll back into product after applying.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Sheetrock, Wallboard, Masonry Block, Ceiling tile:
1 coat Drywall Primer 54400
2 coats Latex California Paints Preference Eggshell #507xx.

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.

Preference Interior Paint Eggshell - 507 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.

Technical Data

Product Type	Finish
Exposure	Interior
Specular Gloss	8° ± 3
Volume Solids	28% ± 2
Weight Solids	41% ± 2
Vehicle Solids	7.4% ± 2
Pigment	23% ± 2
Wet Film Thickness	4 mils
Dry Film Thickness	1 mils
Viscosity @ 77 °F	95KU ± 5
Max VOC	150 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	300-400 s.f./gal.
Porous	250-300 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	4 hours
To Recoat	2 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H.)

Surface Temperature At Application

Maximum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" - 1/2" Nap
Airless Spray	.017 to .019 Tip

Available Package Sizes

5 Gallon	Gallon
(Weight Per Gallon: 11.35 lbs. ± .5 lb)	

Available Colors and Bases

Tintable White	
Available in 1 stock colors	