

Fres~Coat Premium Interior Paint & Primer Matte - 535 Series

Product Description

Fres~Coat 100% Acrylic Paint and Primer in One is a premium smooth flowing, quick drying latex finish paint that is used for interior walls and ceilings. This product contains a self priming feature that will make any paint job go faster in less coats and look better than competitive latex paints. Fres~Coat Matte is an anti-spatter finish designed to provide better wash-ability than conventional flat paints.

Recommended Use

Plaster, sheet rock, wallboard, concrete, masonry block, wood, primed metal, galvanized metal, acoustical surfaces.

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

Plaster, Veneer Plaster (Blueboard) - New plaster must be fully cured and should be wiped with a wet sponge to neutralize any "hot spots". The moisture content should be below 15%. Full plaster requires a minimum of 30 days, skim coat plaster a minimum of 10 days to cure. Nibs should be knifed off before painting. Do not sand until after the surface is coated.

Ferrous Metal - Clean, then prime with FixAll Rust Inhibiting Metal Primer.

New Wood - Knots and stains should be sealed with Wipeout II Oil Based Stain-blocking Primer #20100, Nextech Waterborne Alkyd Stainkill 20701 or Wipeout Latex Stain-blocking Primer 52500 to avoid staining.

Application

California Fres~Coat 100% Acrylic Latex is self-priming over bare sheet rock, composition board, ceiling tile and concrete.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Wallboard, Sheetrock:

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Concrete, Non-Porous Masonry:

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Porous Masonry and Block:

1 coat FixAll Block Filler F37500

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Ferrous Metal - Galvanized:

1 coat FixAll Rust Inhibiting Metal Primer F601xx

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Wood:

1 coat Prime Choice™ All Surface Acrylic Primer 50300

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Acoustical Tile:

2 coats Fres~Coat 100% Acrylic Matte Finish 535XX

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Fres~Coat Premium Interior Paint & Primer Matte - 535 Series

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. All cans should be intermixed and stirred well to achieve continual uniformity.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.

Fres~Coat Premium Interior Paint & Primer Matte - 535 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: www.osha.gov/dsg/topics/silicacrystalline.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable

Technical Data	
Product Type	Finish
Exposure	Interior
Specular Gloss	3° ± 2
Volume Solids	27.9% ± 2
Weight Solids	44.2% ± 2
Vehicle Solids	69.3% ± 2
Pigment	30.7% ± 2
Wet Film Thickness	4.5 mils
Dry Film Thickness	1.2 mils
Viscosity @ 77 °F	98KU ± 3
Max VOC	50 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water
Surface Spread Rate	
Smooth	400-450 s.f./gal.
Porous	300-350 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
To Touch	1 hour
To Handle	8 hours
To Recoat	2 hours
To Wash	14 days
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 100°F	
Tools & Equipments	
Brush	Synthetic, Nylon or Polyester
Roller	3/8" - 1/2" Nap
Airless Spray	
Available Package Sizes	
5 Gallon	Quart
Gallon	
<i>(Weight Per Gallon:10.8 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Pastel Base	Medium Base
Deep Base	Neutral Base
Available in 0 stock colors	

Fres~Coat Premium Interior Paint & Primer Matte - 535 Series

Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.