

Texture Finish - 562 Series

Product Description

This heavy bodied latex finish can be used to create unique and distinctive textured patterns on ceilings and walls. It will hide hair line cracks and minor imperfections and may be painted over with any latex to provide a colored smooth textured finish.

Recommended Use

Plaster, sheetrock, wallboard, masonry, plywood.

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. Texture Paint is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Ferrous Metal - Clean, then prime with Larcoloid[®] Rust Inhibiting Metal Primer

Wood - Seal knots and stains with Prime Choice[™] Low Odor Oil Base Primer Sealer or Prime Choice[™] 100% Acrylic Universal Primer

Masonry Block - Apply one coat of Mason-Cote[®] Block Filler 3751 if a denser surface is desired.

Previously Painted Surfaces - Wash, sand or dust to obtain a paintable surface.

Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.

Application

Brush - White Fiber

Roller: Stipple, 1 mg Nap, Texturing Tools

Direct from container.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse.

Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Wallboard, Sheetrock, Concrete, Non-Porous Masonry:

1 coat Prime Choice[™] All Surface Acrylic Primer 50300

1 coat Texture Paint 56200

or

1 coat Texture Paint 56200

Porous Masonry and Block:

1 coat Mason-Cote[®] Block Filler 3751

1 coat Texture Paint 56200

Wood:

1 coat Prime Choice[™] All Surface Acrylic Primer 50300

1 coat Texture Paint 56200

Note: If a distinctive or different texture is desired, a small test patch should be done to determine the desired appearance.

Precautions

Texture Finish - 562 Series

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.

Keep from freezing.

Texture Finish - 562 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Specialty
Exposure	Interior
Specular Gloss	4° ± 2
Volume Solids	26% ± 2
Weight Solids	44% ± 2
Vehicle Solids	62% ± 2
Pigment	38% ± 2
Wet Film Thickness	38 mils
Dry Film Thickness	10 mils
Viscosity @ 77 °F	125KU ± 5
Max VOC	50 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	50-100 s.f./gal.
Porous	30-50 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	8 hours
To Recoat	4 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H.)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	Stipple, Long nap, Texturing tools
Airless Spray	Not Recommended

Available Package Sizes

Gallon
(Weight Per Gallon: 11.2 lbs. ± .5 lb)

Available Colors and Bases

Available in 0 stock colors