

Ultra Aquaborne Ceramic Interior Finish Matte - 754 Series

Product Description

Ultra Aquaborne Ceramic Premium Matte Finish is a 100% Acrylic Ceramic microsphere wall finish that offers superior flat washability and stain resistance. Its unique formulation provides exceptional hiding power along with its ceramic additive provides additional ease of application, flow and leveling, durability and wash-ability as well as excellent adhesion that puts it in the top of its class. It provides excellent color retention, non-yellowing film and moisture resistance, thus making it the ideal coating for any room in the home, office or commercial building.

Recommended Use

Use on all interior new or previously painted surfaces, such as wood, brick, stone, concrete, cement block, plaster, wallboard and other drywall construction as well as metal.

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Galvanized Metal should be properly prepared prior to coating. A test patch should be done to ensure proper adhesion.

Wood - Seal knots and stains with Alkyd Stain Killer F20400

Application

Ultra Aquaborne Ceramic is ready to use from the container. Ultra Aquaborne Ceramic is self-priming over bare Sheetrock, composition board, ceiling tile and concrete. Specific primers are recommended for new wood, stained and other unique substrate conditions. Avoid brushing back into paint after it has been on the surface for more than five minutes. Allow paint to dry completely before touching up.

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

General Interior Surfaces:

Drywall, Plaster, Wallboard, Primed Metal, Galvanized Metal:

2 coats of Ultra Aquaborne Ceramic Matte 754xx

Wood:

Prime with Alkyd Vapor Barrier Primer & Sealer 20200 or ASAP Enamel Undercoater 50300

2 coats of Ultra Aquaborne Ceramic Matte 754xx

Tile:

1 coat FixAll GripCoat Bonding Primer F50700

2 coats of Ultra Aquaborne Ceramic Matte 754xx

Precautions

Keep from freezing. Do not apply when temperature is below 50°F.

Ultra Aquaborne Ceramic Interior Finish Matte - 754 Series

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.

Environmental Health and Safety Information

Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use with adequate ventilation.

Refer to Safety Data Sheet for additional health and safety information.

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

Ultra Aquaborne Ceramic Interior Finish Matte - 754 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: www.osha.gov/dsg/topics/silicacrystalline.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable

Ultra Aquaborne Ceramic Interior Finish Matte - 754 Series

Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.

Not recommended inside showers, saunas, or steam rooms or where water can accumulate on surface. Do not use showers in bathrooms for 72 hours after application to insure proper adhesion.

Technical Data

Product Type	Finish
Exposure	Interior/ Exterior
Specular Gloss	2° ± 2
Volume Solids	41.27% ± 2
Weight Solids	58.6% ± 2
Vehicle Solids	29.33% ± 2
Pigment	70.67% ± 2
Wet Film Thickness	4.0 mils
Dry Film Thickness	1.6 mils
Viscosity @ 77 °F	98KU ± 3
Max VOC	50 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	350-400 s.f./gal.
Porous	300-350 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	8 hours
To Recoat	4-6 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" - 1/2" Nap
Airless Spray	.017 to .019 Tip

Available Package Sizes

5 Gallon	Gallon
Quart	

(Weight Per Gallon: 11.83 lbs. ± .5 lb)

Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base
Super Hide White	

Available in 0 stock colors

Ultra Aquaborne Ceramic Interior Finish Matte - 754 Series