

## Malibu Premium Interior Finish Eggshell - 785 Series



### Product Description

Malibu Premium Interior Eggshell Finishes are high performing, low odor coatings that are designed for ease in application. Malibu's anti-spatter and quick drying properties make it ideal for occupied spaces. Malibu Acrylic Interior Finishes are high performing, virtually odorless coatings that are designed for ease in application. Malibu\* Eggshell is a great choice for an affordable washable finish in homes, schools, businesses and institutions.

### Recommended Use

Plaster, sheet rock, wallboard, concrete, masonry block, wood, primed metal, primed galvanized metal, acoustical surfaces.

### General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Galvanized Metal should be properly prepared prior to coating. A test patch should be done to ensure proper adhesion.

Wood - Seal knots and stains with an Oil Stain Killing Primer.

### Application

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

Brush: Use nylon or synthetic bristle brushes for best results. Avoid brushing back into paint after it has been on the surface for more than five minutes. Allow paint to dry completely before touching up.

Roller: For best results, use a good quality 3/8 inch nap roller for smooth surfaces and 1/2 inch or longer nap for rougher surfaces. Be sure to allow paint to dry before touching up.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Plaster, Wallboard, Sheetrock:

1 coat of FixAll Muralo 563 Enamel & Undercoater F74700

2 coats Malibu Premium Interior Eggshell 785XX

Concrete, Non-Porous Masonry:

1 coat ASAP Enamel Undercoater 50300

2 coats Malibu Premium Interior Eggshell 785XX

Porous Masonry and Block:

1 coat FixAll Latex Block Filler F51500

2 coats Malibu Premium Interior Eggshell 785XX

Galvanized Metal

1 coat FixAll GripCoat Bonding Primer F50700

2 coats Malibu Premium Interior Eggshell 785XX

Wood:

1 coat FixAll Muralo 563 Enamel & Undercoater F74700

## Malibu Premium Interior Finish Eggshell - 785 Series



2 coats Malibu Premium Interior Eggshell 785XX  
Acoustical Tile:  
2 coats Malibu Premium Interior Eggshell 785XX

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

### Environmental Health and Safety Information

**Keep out of reach of children. Do not take internally. Close container after each use.  
Refer to Safety Data Sheet for additional health and safety information.**

Keep from freezing. Do not apply when temperature is below 50°F.

## Malibu Premium Interior Finish Eggshell - 785 Series



\*Based upon ASTM D6886 testing. Product meets or exceeds current OTC VOC standards ([www.otcair.org](http://www.otcair.org)). VOC testing performed on product formulation prior to application. The product may produce emissions and odors during application, curing and for some time afterwards. Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

This product meets odor testing standards in order to achieve Green Wise Certification by the Coating Research Group Inc. CRGI Test Method 78.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.

### Technical Data

<b>Product Type</b>	Finish
<b>Exposure</b>	Interior
<b>Specular Gloss</b>	8° ± 2
<b>Volume Solids</b>	42% ± 2
<b>Weight Solids</b>	55% ± 2
<b>Vehicle Solids</b>	62% ± 2
<b>Pigment</b>	37% ± 2
<b>Wet Film Thickness</b>	3.0 mils
<b>Dry Film Thickness</b>	1.6 mils
<b>Viscosity @ 77 °F</b>	95KU ± 5
<b>Max VOC</b>	100 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water

### Surface Spread Rate

<b>Smooth</b>	400 s.f./gal.
<b>Porous</b>	300-350 s.f./gal.

(Spray Application is 50% of above)

### Drying Times

<b>To Touch</b>	1 hour
<b>To Handle</b>	2 hours
<b>To Recoat</b>	2-4 hours
<b>To Wash</b>	14 days

(@ 70 - 77 °F, 50% R.H.)

### Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

### Storage Temperature

Store Between Over 40°F to Under 100°F

### Tools & Equipments

<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" Nap Synthetic Fiber
<b>Airless Spray</b>	.017 to .019 Tip

### Available Package Sizes

5 Gallon	Gallon
Quart	
(Weight Per Gallon: 11.5 lbs. ± .5 lb)	

### Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base
Super Hide White	

## Malibu Premium Interior Finish Eggshell - 785 Series



Available in 0 stock colors