

## ProPaint Interior Finish Semi Gloss - 510 Series

### Product Description

ProPaint Semi-Gloss is a smooth flowing latex semi-gloss enamel developed to provide an attractive, scrubbable finish for high use areas in homes, schools, commercial and public buildings. This anti-spatter formulation dries quickly to a velvety smooth finish ideal for most interior surfaces.

### Recommended Use

Plaster, sheetrock, wallboard, concrete, masonry block, wood, primed metal, primed galvanized metal.

### General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with Spackle or an appropriate patching compound.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Galvanized Metal - Clean, then prime with FixAll Ultimate Universal Primer F50600

Wood - Seal knots and stains with FixAll Alkyd Stain Killer F20400

Masonry Block - Apply one coat of ProPaint Block Filler F51500 if a denser surface is desired.

### Application

ProPaint is ready to use from the container. ProPaint Semi-Gloss is self-priming over bare Sheetrock, composition board, ceiling tile and concrete. Specific primers are recommended for new wood, stained and other unique substrate conditions.

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting.

The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Plaster, Wallboard, Sheetrock:

1 coat FixAll PVA Drywall Primer F54400

2 coats ProPaint Semi-Gloss 510XX

Concrete, Non-Porous Masonry:

1 coat PrimeTouch Primer and Sealer 54500

2 coats ProPaint Semi-Gloss 510XX

Porous Masonry and Block:

1 coat FixAll Latex Block Filler F51500

2 coats ProPaint Semi-Gloss 510XX

Ferrous Metal - Galvanized Metal:

1 coat Fixall Alkyd Stain Killer F20400

2 coats ProPaint Semi-Gloss 510XX

Wood:

1 coat CalPro Low VOC Primer & Sealer 65500

2 coats ProPaint Semi-Gloss 510XX

Acoustical Tile:

2 coats ProPaint Semi-Gloss 510XX

## ProPaint Interior Finish Semi Gloss - 510 Series

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

### Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.  
Refer to Safety Data Sheet for additional health and safety information.

## ProPaint Interior Finish Semi Gloss - 510 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: [www.osha.gov/dsg/topics/silicacrystalline](http://www.osha.gov/dsg/topics/silicacrystalline).

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable

Technical Data	
<b>Product Type</b>	Finish
<b>Exposure</b>	Interior
<b>Specular Gloss</b>	45° ± 5
<b>Volume Solids</b>	26.31% ± 2
<b>Weight Solids</b>	37.47% ± 2
<b>Vehicle Solids</b>	50.79% ± 2
<b>Pigment</b>	49.21% ± 2
<b>Wet Film Thickness</b>	4.5 mils
<b>Dry Film Thickness</b>	1.2 mils
<b>Viscosity @ 77 °F</b>	98KU ± 3
<b>Max VOC</b>	100 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	350-400 s.f./gal.
<b>Porous</b>	250-300 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
<b>To Touch</b>	1 hour
<b>To Handle</b>	8 hours
<b>To Recoat</b>	4 hours
<b>To Wash</b>	14 days
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 100°F	
Tools & Equipments	
<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" Nap Synthetic Fiber
<b>Airless Spray</b>	.017 to .019 Tip
Available Package Sizes	
5 Gallon	Gallon
<i>(Weight Per Gallon:9.84 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Pastel Base	Medium Base
Deep Base	Neutral Base
Super Hide White	
Available in 3 stock colors	

## ProPaint Interior Finish Semi Gloss - 510 Series

Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.